

14A-5.0-16B14 Information

Heisener.com

Part Number 14A-5.0-16B14

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 5VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









14A-5.0-16B14 Specifications

Manufacturer Part Number14A-5.0-16B14ManufacturerPulse Electronics PowerCategoryTransformersPower TransformersPower TransformersPackage-SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 620mA, Series 310mAPrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WVoltage - Isolation-		
CategoryTransformersPackage-SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 620mA, Series 310mAPrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)34.93mm	Manufacturer Part Number	14A-5.0-16B14
Package - Series International PC Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 620mA, Series 310mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max)	Manufacturer	Pulse Electronics Power
Package - International PC Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 620mA, Series 310mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 34.93mm	Category	Transformers
Series International PC Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 620mA, Series 310mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 34.93mm		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 620mA, Series 310mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 34.93mm	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 620mA, Series 310mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max)	Series	International PC Plug-In
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 620mA, Series 310mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Parallel 620mA, Series 310mA Dual Single, Multiple Taps No Power No Power Power Power Au Au Au Au Au Au Au Au Au A	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Dual Single, Multiple Taps No POP No 1 VA POP POP Through Hole PC Pin 34.93mm	Voltage - Secondary (Full Load)	Parallel 8V, Series 16V
Secondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)34.93mm	Current - Output (Max)	Parallel 620mA, Series 310mA
Center TapNoPower - Max5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)34.93mm	Primary Winding(s)	Dual
Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 34.93mm	Secondary Winding(s)	Single, Multiple Taps
Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 34.93mm	Center Tap	No
Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 34.93mm	Power - Max	5 VA
Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 34.93mm	Mounting Type	Through Hole
Height - Seated (Max) 34.93mm	Termination Style	PC Pin
-	Size / Dimension	41.28mm L x 33.32mm W
Voltage - Isolation -	Height - Seated (Max)	34.93mm
	Voltage - Isolation	-
Weight 0.37 lb (167.83g)	Weight	0.37 lb (167.83g)
Report errors?		Report errors?

14A-5.0-16B14 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

14A-5.0-16B14 Payment Methods

































If you have any question about 14A-5.0-16B14, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com