

15.5CAV2E Information

Heisener.com

Part Number 15.5CAV2E

Manufacturer Eaton

Category

Circuit Protection

Electrical, Specialty Fuses

Description FUSE 5.5KV 2A 12" 1434 Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









15.5CAV2E Specifications

Manufacturer Part Number 15.5CAV2E Manufacturer Eaton Category Circuit Protection Package Cartridge, Non-Standard Series * Fuse Type - Current Rating - Voltage Rating - AC - Voltage Rating - DC - Response Time - Applications - Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.626" Dia x 12.870" L (41.30mm x 326.90mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series * Fuse Type - Current Rating - Voltage Rating - AC - Voltage Rating - DC - Response Time - Applications - Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.626" Dia x 12.870" L (41.30mm x 326.90mm)	Manufacturer Part Number	15.5CAV2E
PackageCartridge, Non-StandardSeries*Fuse Type-Current Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.626" Dia x 12.870" L (41.30mm x 326.90mm)	Manufacturer	Eaton
Package Cartridge, Non-Standard Series * Fuse Type - Current Rating - Voltage Rating - AC - Voltage Rating - DC - Response Time - Applications - Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.626" Dia x 12.870" L (41.30mm x 326.90mm)	Category	Circuit Protection
Series * Fuse Type - Current Rating - Voltage Rating - AC - Voltage Rating - DC - Response Time - Applications - Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.626" Dia x 12.870" L (41.30mm x 326.90mm)		Electrical, Specialty Fuses
Fuse Type - Current Rating - Current Rating - Current Rating - Coltage Rating - AC - Current Rating - Coltage Rating - DC - Current Rating - DC - Current Rating - Current Ratin	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time - Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Curridge, Non-Standard 1.626" Dia x 12.870" L (41.30mm x 326.90mm)	Series	*
Voltage Rating - AC Voltage Rating - DC Response Time Applications Features - Class Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Voltage Rating - AC - - - - - - - - - - - - -	Fuse Type	-
Voltage Rating - DC Response Time - Applications - Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cauthor Size / Dia x 12.870" L (41.30mm x 326.90mm)	Current Rating	-
Response Time Applications Features Class Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension	Voltage Rating - AC	-
Applications - Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.626" Dia x 12.870" L (41.30mm x 326.90mm)	Voltage Rating - DC	-
Features - Class - Class - Component of the Component of	Response Time	-
Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage - Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.626" Dia x 12.870" L (41.30mm x 326.90mm)	Applications	-
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Holder Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.626" Dia x 12.870" L (41.30mm x 326.90mm)	Features	-
Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.626" Dia x 12.870" L (41.30mm x 326.90mm)	Class	-
Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.626" Dia x 12.870" L (41.30mm x 326.90mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.626" Dia x 12.870" L (41.30mm x 326.90mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 1.626" Dia x 12.870" L (41.30mm x 326.90mm)	Breaking Capacity @ Rated Voltage	-
Size / Dimension 1.626" Dia x 12.870" L (41.30mm x 326.90mm)	Mounting Type	Holder
· · · · · · · · · · · · · · · · · · ·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	1.626" Dia x 12.870" L (41.30mm x 326.90mm)
		Report errors?

15.5CAV2E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

15.5CAV2E Payment Methods





















15.5CAV2E Shipping Methods













If you have any question about 15.5CAV2E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com