

# **15 PSI-D-HGRADE-MV**

#### **15 PSI-D-HGRADE-MV Information**



Part Number	15 PSI-D-HGRADE-MV	
Manufacturer	All Sensors Corporation	
Category	Sensors, Transducers Pressure Sensors, Transducers	
Description	SENSOR 15PSID MV DUAL	
Package	6-SIP Module	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **15 PSI-D-HGRADE-MV Specifications**

Manufacturer Part Number     15 PSI-D-HGRADE-MV       Manufacturer     All Sensors Corporation       Category     Sensors, Transducers       Package     6-SIP Module       Series     AXCX       Pressure Type     Differential       Operating Pressure     15 PSI (103.42 kPa)       Output Type     Wheatstone Bridge       Output Type     0 mV ~ 90 mV (12V)       Accuracy     ±0.5%       Voltage - Supply     16V       Port Size     Temperature Compensated       Factures     Temperature Compensated       Pressure Compensated     60 PSI (413.69 kPa)       Operating Temperature     -25°C ~ 85°C       Package / Case     6.SIP Module		
CategorySensors, TransducersPackagePressure Sensors, TransducersPackage6-SIP ModuleSeriesAXCXPressure TypeDifferentialOperating PressureNeatsone BridgeOutput TypeWheatsone BridgeOutput Type0mV ~90 mV (12V)Accuracy4.05%Voltage - Supply16VPort SizeMale - 0.19" (4.83mm) Tube, DualFeaturesTemperature CompensatedTermination Style6.9SI (413.69 kPa)Maximum Pressure6.9SI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6.9IP ModuleSupplier Device Package-	Manufacturer Part Number	15 PSI-D-HGRADE-MV
Pressure Sensors, TransducersPackage6-SIP ModuleSeriesAXCXPressure TypeDifferentialOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput Type0 mV ~ 90 mV (12V)Accuracy±0.5%Voltage - Supply16VPort SizeMale - 0.19" (4.83mm) Tube, DualPort StyleEmperature CompensatedFeatures70PSI (413.69 kPa)Maximum Pressure60 PSI (413.69 kPa)Operating Temperature-55°C ~ 85°CPackage / Case6-SIP ModuleSupplier Device Package-	Manufacturer	All Sensors Corporation
Package6-SIP ModuleSeriesAXCXPressure TypeDifferentialOperating Pressure15 PSI (103.42 kPa)Output TypeWheatsone BridgeOutput Type0 mV ~ 90 mV (12V)Accuracy±0.5%Voltage - SupplyIde - 0.19" (4.83mm) Tube, DualPort SizeBarblessFeaturesPengrature CompensatedMaximum Pressure0 nSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6.19 ModuleSupplier Device Package-	Category	Sensors, Transducers
SeriesAXCXPressure TypeDiffeentialOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput Output0 mV ~ 90 mV (12V)Accuracy±0.5%Voltage - Supply16VPort SizeMale - 0.19" (4.83mm) Tube, DualPort StyleBarblessFeaturesTemperature CompensatedPoreating Temperature60 PSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6.SIP ModuleSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeDifferentialOperating Pressure15 PSI (103.42 kPa)Output TypeWheatsone BridgeOutput Output0 mV ~ 90 mV (12V)Accuracy±0.5%Voltage - Supply16VPort SizeMale - 0.19" (4.83mm) Tube, DualPort StyleBarblessFeaturesPCBMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6.SIP ModuleSupplier Device Package-	Package	6-SIP Module
NumerativeInternational presentOperating Pressure15 PSI (103.42 kPa)Output TypeWheatsone BridgeOutput0 mV ~ 90 mV (12V)Accuracy±0.5%Voltage - Supply16VPort SizeMale - 0.19" (4.83mm) Tube, DualPort StyleBarblessFeaturesTemperature CompensatedPort Style60 PSI (413.69 kPa)Maximum Pressure60 PSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6-SIP ModuleSupplier Device Package-	Series	AXCX
Output TypeWheatstone BridgeOutput0 mV ~ 90 mV (12V)Accuracy±0.5%Voltage - Supply16VPort SizeMale - 0.19" (4.83mm) Tube, DualPort StyleBarblessFeaturesTemperature CompensatedTermination Style60 PSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6-SIP ModuleSupplier Device Package-	Pressure Type	Differential
Output0 mV ~ 90 mV (12V)Accuracy±0.5%Voltage - Supply16VPort SizeMale - 0.19" (4.83mm) Tube, DualPort StyleBarblessFeaturesTemperature CompensatedTermination Style60 PSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6-SIP ModuleSupplier Device Package-	Operating Pressure	15 PSI (103.42 kPa)
Accuracy±0.5%Accuracy16VVoltage - Supply16VPort SizeMale - 0.19" (4.83mm) Tube, DualPort StyleBarblessFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6-SIP ModuleSupplier Device Package-	Output Type	Wheatstone Bridge
Voltage - Supply16VPort SizeMale - 0.19" (4.83mm) Tube, DualPort StyleBarblessFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6-SIP ModuleSupplier Device Package-	Output	0 mV ~ 90 mV (12V)
Port SizeMale - 0.19" (4.83mm) Tube, DualPort StyleBarblessFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6-SIP ModuleSupplier Device Package-	Accuracy	±0.5%
Port StyleBarblessFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6-SIP ModuleSupplier Device Package-	Voltage - Supply	16V
FeaturesTemperature CompensatedTermination StylePCBMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6-SIP ModuleSupplier Device Package-	Port Size	Male - 0.19" (4.83mm) Tube, Dual
Termination StylePCBMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6-SIP ModuleSupplier Device Package-	Port Style	Barbless
Maximum Pressure60 PSI (413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case6-SIP ModuleSupplier Device Package-	Features	Temperature Compensated
Operating Temperature-25°C ~ 85°CPackage / Case6-SIP ModuleSupplier Device Package-	Termination Style	PCB
Package / Case 6-SIP Module   Supplier Device Package -	Maximum Pressure	60 PSI (413.69 kPa)
Supplier Device Package -	Operating Temperature	-25°C ~ 85°C
	Package / Case	6-SIP Module
Report errors?	Supplier Device Package	-
		Report errors?

#### **15 PSI-D-HGRADE-MV Guarantees**



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

စာ MoneyGram <u>Alipay</u> VISA

DISCOVER

#### 15 PSI-D-HGRADE-MV Payment Methods



### **15 PSI-D-HGRADE-MV Shipping Methods**



If you have any question about 15 PSI-D-HGRADE-MV, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com

UNION

 $\mathbf{M}$