

15 PSI-G-4V-PRIME

15 PSI-G-4V-PRIME Information



Part Number15 PSI-G-4V-PRIMEManufacturerAll Sensors CorporationCategorySensors, Transducers
Pressure Sensors, TransducersDescriptionSENSOR 15PSIG 4V DUALPackage4-SIP Module
For the pricing/inventory/lead time, please contact
us
Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



15 PSI-G-4V-PRIME Specifications

Manufacturer Part Number15 PSI-G-4V-PRIMEManufacturerAll Sensors CorporationCategorySensors, TransducersPackage4-SIP ModuleSeriesAXCAPressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog VoltageOutput Type0.25 V ~ 4.25 VAccuracy4.51V ~ 5.5 VPort SizeBarblessFort StyleBarblessFeaturesAmalified Output, Temperature CompensatedPort StyleSerblessFeatures4.5 PSI (310.26 kPa)Operating Tressure4.5 PSI (310.26 kPa)Operating Temperature4.5 PSI (310.26 kPa)Operating Temperature4.5 PSI (310.26 kPa)Port Style3.5 PSI (310.26 kPa)Maximum Pressure4.5 PSI (310.26 kPa)Operating Temperature4.5 PSI (310.26 kPa)Port StyleSerblessStyle Pressure3.5 PSI (310.26 kPa)Port Style Pressure4.5 PSI (310.26 kPa)Port Style Pressure4.5 PSI (310.26 kPa)Port Style Pressure4.5 PSI (310.26 kPa)Port Style Pressure5.5 PSI (5.5 PSI (5.5 kPa)Port Style Pressure5.5 PSI (5.5 kPa)Port		
CategorySensors, TransducersPackage4-SIP ModuleSeriesAXCAPressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - SupplyAsde - 0.19" (4.8mm) TubePort SizeMale - 0.19" (4.8mm) TubeFeaturesAmplified Output, Temperature CompensatedTermination Style9CBMaximum Pressure4.5 ISI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-	Manufacturer Part Number	15 PSI-G-4V-PRIME
PackagePressure Sensors, TransducersPackage4-SIP ModuleSeriesAXCAPressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - SupplyAsch - 0.19" (4.8mm) TubePort SizeBarblessFeaturesAmplified Output, Temperature CompensatedPort Style4.5 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-	Manufacturer	All Sensors Corporation
Package4-SIP ModuleSeriesAXCAPressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedMaximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-	Category	Sensors, Transducers
SeriesAXCASeriesAXCAPressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog VoltageOutput Type0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedMaximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog VoltageOutput Output0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAcplified Output, Temperature CompensatedPremination Style45 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4.5IP ModuleSupplier Device Package-	Package	4-SIP Module
Operating Pressure15 PSI (103.42 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedMaximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4.5IP ModuleSupplier Device Package-	Series	AXCA
Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure-40°C ~ 125°CPackage / Case4.5IP ModuleSupplier Device Package-	Pressure Type	Vented Gauge
Output0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Operating Pressure	15 PSI (103.42 kPa)
Accuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Output Type	Analog Voltage
Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Output	0.25 V ~ 4.25 V
Port SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Accuracy	$\pm 0.5\%$
Port StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Voltage - Supply	4.5 V ~ 5.5 V
FeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Port Size	Male - 0.19" (4.8mm) Tube
Termination StylePCBMaximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Port Style	Barbless
Maximum Pressure45 PSI (310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Termination Style	PCB
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	45 PSI (310.26 kPa)
Supplier Device Package -	Operating Temperature	$-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$
	Package / Case	4-SIP Module
	Supplier Device Package	-
Rep		Report errors?

15 PSI-G-4V-PRIME Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

15 PSI-G-4V-PRIME Payment Methods





If you have any question about 15 PSI-G-4V-PRIME, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com