

1500774 Information



For Reference Only

Part Number 1500774

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Circular Connectors

Description CONN M12 5POS PLUG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1500774 Specifications

Manufacturer Part Number1500774ManufacturerPhoenix ContactCategoryConnectors, InterconnectsPackage-SeriesSACCConnector TypePlug, Male PinsNumber of Positions5Shell Size - InsertM12-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypeThreadedOrientationAIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, Finish-Contact Finish-Features-Voltage - Rated60VCurrent Rating4A		
Category Circular Connectors Circular Connectors Package - Series SACC Connector Type Plug, Male Pins Number of Positions Shell Size - Insert M12-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation A Ingress Protection Shell Material, Finish Plastic Contact Finish - Features - Voltage - Rated Current Rating Connectors, Interconnects Connectors SACC Connectors NACC Plug, Male Pins NI2-5 Plug, Male Pins NI2-5 Plug, Male Pins NI2-5 Plug, Male Pins NI2-5 Pree Hanging (In-Line) Free Hanging	Manufacturer Part Number	1500774
Circular Connectors Package - Series SACC Connector Type Plug, Male Pins Number of Positions Shell Size - Insert M12-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation A Ingress Protection Shell Material, Finish Plastic Contact Finish - Features - Voltage - Rated Output Current Rating Cannot Connectors SACC Plug, Male Pins And Angle Pins Angl	Manufacturer	Phoenix Contact
Package-SeriesSACCConnector TypePlug, Male PinsNumber of Positions5Shell Size - InsertM12-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypeThreadedOrientationAIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPlasticContact Finish-Features-Voltage - Rated60VCurrent Rating4A	Category	Connectors, Interconnects
Series SACC Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert M12-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation A Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Plastic Contact Finish - Features Voltage - Rated 60V Current Rating 4A		Circular Connectors
Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert M12-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation A Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Plastic Contact Finish - Features - Voltage - Rated 60V Current Rating 4A	Package	-
Number of Positions Shell Size - Insert M12-5 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation A Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Plastic Contact Finish - Features Voltage - Rated Current Rating 4A	Series	SACC
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation A Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Plastic Contact Finish - Features - Voltage - Rated Current Rating M12-5 M12-5 Free Hanging (In-Line) A Ingress (In-Line) Free Hanging (In-L	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation A Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Plastic Contact Finish - Features - Voltage - Rated Current Rating 4A	Number of Positions	5
Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypeThreadedOrientationAIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPlasticContact Finish-Features-Voltage - Rated60VCurrent Rating4A	Shell Size - Insert	M12-5
Termination Screw Fastening Type Threaded Orientation A Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Plastic Contact Finish - Features - Voltage - Rated 60V Current Rating 4A	Shell Size, MIL	-
Fastening Type Orientation A Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Plastic Contact Finish - Features - Voltage - Rated Current Rating A Threaded A	Mounting Type	Free Hanging (In-Line)
Orientation A Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Plastic Contact Finish - Features - Voltage - Rated 60V Current Rating 4A	Termination	Screw
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Plastic Contact Finish - Features - Voltage - Rated 60V Current Rating 4A	Fastening Type	Threaded
Shell Material, Finish Contact Finish - Features - Voltage - Rated Current Rating Plastic 60V 4A	Orientation	A
Contact Finish - Features - Voltage - Rated 60V Current Rating 4A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 60V Current Rating 4A	Shell Material, Finish	Plastic
Voltage - Rated 60V Current Rating 4A	Contact Finish	-
Current Rating 4A	Features	-
	Voltage - Rated	60V
Report errors?	Current Rating	4A
		Report errors?

1500774 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1500774 Payment Methods





















1500774 Shipping Methods













If you have any question about 1500774, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com