

150224-6002-RB

150224-6002-RB Information

Categor	cturer 3M y Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
Descript	ion CONN 24POS 2MM SOCKET VERT PC MT	26.69.65
Package	-	
	For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



150224-6002-RB Specifications

Manufacturer Part Number150224-6002-RBManufacturer3MCategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series1502Connector TypeReceptacleContact TypeReceptacleSortat TypeBoard to Board or CableNumber of Positions LoadedAlNumber of Positions Loaded0.079" (2.00mm)Number of Rows2Row Spacing - MatingOlderMounting TypePhough HoleFernales ColderSolderFerning TypeSolderStation ColorSolderStation Frish - MatingOldor (3.0000)Station ColorBlackStation ColorBlackStation ColorSolderStation ColorSolderStation ColorSolderStation Frish Thickness - MatingOly (2.54mm)Station Fleight0.17" (4.50mm)Station FleightSolderStation FleightSolderStation FleightSolderStation FleightSolderStation FleightSolderStation FleightSolderStation Station StationSolderStation FleightSolderStation FleightSolderStation Station StationSolderStation FleightSolderStation FleightSolderStation FleightSolderStation FleightSolderStation FleightSolder <th></th> <th></th>		
Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series 1502 Connector Type Receptacle Contact Type Receptacle Contact Type Board to Board or Cable Number of Positions 24 Number of Positions Loaded All Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Onder You Point You Spacing - Mating 0.019" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.019" (2.00mm) Mounting Type Through Hole You Spacing - Mating Solder You Spacing - Mating	Manufacturer Part Number	150224-6002-RB
InterfactRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series1502Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleFreminationSolderFortaut Finish - MatingGoldContact Finish - MatingGoldSolution ColorBlackInsulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature55°C ~ 105°C	Manufacturer	3M
Package-Series1502Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypeOsderContact Finish - MatingGoldContact Finish Fickness - MatingJoin (0.76µm)Insulation ColorBlackInsulation Height0.17" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature55°C ~ 105°C	Category	Connectors, Interconnects
Series1502Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingSipin (0.76µm)Insulation ColorBlackInsulation Height0.171" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature-55°C ~ 105°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.10" (2.54mm)Contact Length - PostSi0c" C 105°C	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.17" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature-55°C ~ 105°C	Series	1502
StyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature-55°C ~ 105°C	Connector Type	Receptacle
Number of Positions 24 Number of Positions Loaded All Number of Positions Loaded 0.079" (2.00mm) Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type 0.079" (2.00mm) Termination 0.079" (2.00mm) Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Insulation Color Black Insulation Height 0.177" (4.50mm) Contact Length - Post 0.100" (2.54mm) Operating Temperature -55°C ~ 105°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.177" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature-55°C ~ 105°C	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.177" (4.50mm)Contact Length - Post5.5°C ~ 105°C	Number of Positions	24
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature-55°C ~ 105°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJupin (0.76µm)Insulation ColorBlackInsulation Height0.107" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature-55°C ~ 105°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature-55°C ~ 105°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.177" (4.50µm)Contact Length - Post0.100" (2.54µm)Operating Temperature-55°C ~ 105°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature-55°C ~ 105°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature-55°C ~ 105°C	Termination	Solder
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature-55°C ~ 105°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.100" (2.54mm)Operating Temperature-55°C ~ 105°C	Contact Finish - Mating	Gold
Insulation Height 0.177" (4.50mm) Contact Length - Post 0.100" (2.54mm) Operating Temperature -55°C ~ 105°C	Contact Finish Thickness - Mating	30µin (0.76µm)
Contact Length - Post0.100" (2.54mm)Operating Temperature-55°C ~ 105°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 105^{\circ}C$	Insulation Height	0.177" (4.50mm)
	Contact Length - Post	0.100" (2.54mm)
	Operating Temperature	-55°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

150224-6002-RB Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 150224-6002-RB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com