

150E1C8.25 Information

Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Heisener.com

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 150A 8.25KVAC

Package Cartridge, Non-Standard

150E1C8.25

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









150E1C8.25 Specifications

Manufacturer Part Number150E1C8.25ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating150AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating150AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Manufacturer Part Number	150E1C8.25
Backage Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 150A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating150AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating150AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 150A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge R250V (8.25kV)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC	Series	POWR-GARD?
Voltage Rating - AC Voltage Rating - DC Response Time Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 8250V (8.25kV) - Response Time - Response Time - Transformer Protection Indicating E Foretaire Potection Features Indicating Features E Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cautions - Cauting Temperature Cartridge, Non-Standard Size / Dimension - Cauting Temperature Size / Dimension - Cauting Temperature Cauting Type Cauting Type Cartridge, Non-Standard Size / Dimension - Cauting Type Timension - Cauting Type Timensio	Current Rating	150A
Response Time Applications Transformer Protection Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Transformer Protection - Reason Protection Features Beaking Capacity For Approvals - Cartridge, Non-Standard 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Voltage Rating - AC	8250V (8.25kV)
Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Transformer Protection Indicating E BA Holder Class E Cartridge, Non-Standard 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Voltage Rating - DC	-
Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Response Time	-
Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Applications	Transformer Protection
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Class	E
Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	3.000" Dia x 15.875" L (76.20mm x 403.23mm)
		Report errors?

150E1C8.25 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

150E1C8.25 Payment Methods





















150E1C8.25 Shipping Methods













If you have any question about 150E1C8.25, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com