

**151220-2420-TB Information**


For Reference Only

**Part Number** [151220-2420-TB](#)  
**Manufacturer** 3M  
**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Male Pins](#)  
**Description** CONN HEADER 2MM 20PS DL SMD 30AU  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



[Request a Quote](#)

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**151220-2420-TB Specifications**

|                            |                                                                                          |
|----------------------------|------------------------------------------------------------------------------------------|
| Manufacturer Part Number   | <a href="#">151220-2420-TB</a>                                                           |
| Manufacturer               | 3M                                                                                       |
| Category                   | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Male Pins</a> |
| Package                    | -                                                                                        |
| Series                     | 1512                                                                                     |
| Connector Type             | Header                                                                                   |
| Contact Type               | Male Pin                                                                                 |
| Pitch - Mating             | 0.079" (2.00mm)                                                                          |
| Style                      | Board to Board                                                                           |
| Shrouding                  | Unshrouded                                                                               |
| Number of Positions        | 20                                                                                       |
| Number of Positions Loaded | All                                                                                      |
| Number of Rows             | 2                                                                                        |
| Row Spacing - Mating       | 0.079" (2.00mm)                                                                          |
| Mounting Type              | Surface Mount                                                                            |
| Termination                | Solder                                                                                   |
| Fastening Type             | Push-Pull                                                                                |
| Contact Length - Mating    | 0.152" (3.86mm)                                                                          |
| Contact Length - Post      | -                                                                                        |
| Overall Contact Length     | -                                                                                        |
| Insulation Height          | 0.060" (1.52mm)                                                                          |
| Contact Shape              | Square                                                                                   |
| Contact Finish - Mating    | Gold                                                                                     |

|                                   |                                            |
|-----------------------------------|--------------------------------------------|
| Contact Finish Thickness - Mating | 30µin (0.76µm)                             |
| Contact Finish - Post             | Tin-Lead                                   |
| Contact Material                  | Copper Alloy                               |
| Insulation Material               | Liquid Crystal Polymer (LCP), Glass Filled |
| Features                          | -                                          |
| Operating Temperature             | -55°C ~ 105°C                              |
| Ingress Protection                | -                                          |
| Material Flammability Rating      | UL94 V-0                                   |
| Insulation Color                  | Black                                      |
|                                   | <a href="#">Report errors?</a>             |

## 151220-2420-TB Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 151220-2420-TB Payment Methods



## 151220-2420-TB Shipping Methods



If you have any question about 151220-2420-TB, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)