

### 1519-4 Information

www.p.com

For Reference Only

Part Number 1519-4

Manufacturer Keystone Electronics

Category Connectors, Interconnects
Terminals - Turret Connectors

**Description** TERM TURRET HOLLOW L=4.75MM TIN

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 1519-4 Specifications

Manufacturer Part Number         1519-4           Manufacturer         Keystone Electronics           Category         Connectors, Interconnects           Package         -           Series         -           Terminal Type         Single End, Hollow           Number of Turrets         Single           Length - Above Board         0.187" (4.75mm)           Length - Below Flange         0.171" (4.34mm)           Length - Overall         0.358" (9.09mm)           Mounting Type         Through Hole           Termination         Staking Flare           Flange Diameter         0.187" (4.75mm)           Diameter - Turret Head         0.140" (3.56mm)           Staking Side OD         0.110" (2.79mm)           Staking Side ID         -           Mounting Hole Diameter         0.113" (2.87mm)           Board Thickness         0.125" (3.18mm)           Contact Material         Brass           Contact Finish Thickness         -           Insulation         Non-Insulated	<b>-</b>	
Category         Connectors, Interconnects           Package         -           Series         -           Terminal Type         Single End, Hollow           Number of Turrets         Single           Length - Above Board         0.187" (4.75mm)           Length - Below Flange         0.171" (4.34mm)           Length - Overall         0.358" (9.09mm)           Mounting Type         Through Hole           Termination         Staking Flare           Flange Diameter         0.187" (4.75mm)           Diameter - Turret Head         0.140" (3.56mm)           Staking Side OD         0.110" (2.79mm)           Staking Side ID         -           Mounting Hole Diameter         0.113" (2.87mm)           Board Thickness         0.125" (3.18mm)           Contact Material         Brass           Contact Finish         Tin           Contact Finish Thickness         -           Insulation         Non-Insulated	Manufacturer Part Number	1519-4
Package - Cerrinal Type Single End, Hollow Single S	Manufacturer	Keystone Electronics
Package         -           Series         -           Terminal Type         Single End, Hollow           Number of Turrets         Single           Length - Above Board         0.187" (4.75mm)           Length - Below Flange         0.171" (4.34mm)           Length - Overall         0.358" (9.09mm)           Mounting Type         Through Hole           Termination         Staking Flare           Flange Diameter         0.187" (4.75mm)           Diameter - Turret Head         0.140" (3.56mm)           Staking Side OD         0.110" (2.79mm)           Staking Side ID         -           Mounting Hole Diameter         0.113" (2.87mm)           Board Thickness         0.125" (3.18mm)           Contact Material         Brass           Contact Finish         Tin           Contact Finish Thickness         -           Insulation         Non-Insulated	Category	Connectors, Interconnects
Series         -           Terminal Type         Single End, Hollow           Number of Turrets         Single           Length - Above Board         0.187" (4.75mm)           Length - Below Flange         0.171" (4.34mm)           Length - Overall         0.358" (9.09mm)           Mounting Type         Through Hole           Termination         Staking Flare           Flange Diameter         0.187" (4.75mm)           Diameter - Turret Head         0.140" (3.56mm)           Staking Side OD         0.110" (2.79mm)           Staking Side ID         -           Mounting Hole Diameter         0.113" (2.87mm)           Board Thickness         0.125" (3.18mm)           Contact Material         Brass           Contact Finish         Tin           Contact Finish Thickness         -           Insulation         Non-Insulated		Terminals - Turret Connectors
Terminal TypeSingle End, HollowNumber of TurretsSingleLength - Above Board $0.187"$ (4.75mm)Length - Below Flange $0.171"$ (4.34mm)Length - Overall $0.358"$ (9.09mm)Mounting TypeThrough HoleTerminationStaking FlareFlange Diameter $0.187"$ (4.75mm)Diameter - Turret Head $0.140"$ (3.56mm)Staking Side OD $0.110"$ (2.79mm)Staking Side ID-Mounting Hole Diameter $0.113"$ (2.87mm)Board Thickness $0.125"$ (3.18mm)Contact MaterialBrassContact FinishTinContact Finish Thickness-InsulationNon-Insulated	Package	-
Number of TurretsSingleLength - Above Board0.187" (4.75mm)Length - Below Flange0.171" (4.34mm)Length - Overall0.358" (9.09mm)Mounting TypeThrough HoleTerminationStaking FlareFlange Diameter0.187" (4.75mm)Diameter - Turret Head0.140" (3.56mm)Staking Side OD0.110" (2.79mm)Staking Side ID-Mounting Hole Diameter0.113" (2.87mm)Board Thickness0.125" (3.18mm)Contact MaterialBrassContact FinishTinContact Finish Thickness-InsulationNon-Insulated	Series	-
Length - Above Board Length - Below Flange 10.171" (4.34mm) Length - Overall 10.358" (9.09mm) Mounting Type 11. Through Hole Termination 12. Staking Flare Flange Diameter 12. O.187" (4.75mm) Diameter - Turret Head 13. O.140" (3.56mm) Staking Side OD 13. O.110" (2.79mm) Staking Side ID 14. O.113" (2.87mm) Board Thickness 15. O.125" (3.18mm) Contact Material 15. Brass 16. Contact Finish Thickness 17. Contact Finish Thickness 18. Onland Insulated 19. Onland Insulated 10. Onland Insulated 10. Onland Insulated	Terminal Type	Single End, Hollow
Length - Below Flange0.171" (4.34mm)Length - Overall0.358" (9.09mm)Mounting TypeThrough HoleTerminationStaking FlareFlange Diameter0.187" (4.75mm)Diameter - Turret Head0.140" (3.56mm)Staking Side OD0.110" (2.79mm)Staking Side ID-Mounting Hole Diameter0.113" (2.87mm)Board Thickness0.125" (3.18mm)Contact MaterialBrassContact FinishTinContact Finish Thickness-InsulationNon-Insulated	Number of Turrets	Single
Length - Overall0.358" (9.09mm)Mounting TypeThrough HoleTerminationStaking FlareFlange Diameter0.187" (4.75mm)Diameter - Turret Head0.140" (3.56mm)Staking Side OD0.110" (2.79mm)Staking Side ID-Mounting Hole Diameter0.113" (2.87mm)Board Thickness0.125" (3.18mm)Contact MaterialBrassContact FinishTinContact Finish Thickness-InsulationNon-Insulated	Length - Above Board	0.187" (4.75mm)
Mounting TypeThrough HoleTerminationStaking FlareFlange Diameter0.187" (4.75mm)Diameter - Turret Head0.140" (3.56mm)Staking Side OD0.110" (2.79mm)Staking Side ID-Mounting Hole Diameter0.113" (2.87mm)Board Thickness0.125" (3.18mm)Contact MaterialBrassContact FinishTinContact Finish Thickness-InsulationNon-Insulated	Length - Below Flange	0.171" (4.34mm)
Termination Staking Flare  Flange Diameter  Diameter - Turret Head  0.140" (3.56mm)  Staking Side OD  0.110" (2.79mm)  Staking Side ID  - Mounting Hole Diameter  0.113" (2.87mm)  Board Thickness  0.125" (3.18mm)  Contact Material  Brass  Contact Finish  Tin  Contact Finish Thickness  - Insulation  Non-Insulated	Length - Overall	0.358" (9.09mm)
Flange Diameter  Diameter - Turret Head  0.140" (3.56mm)  Staking Side OD  0.110" (2.79mm)  Staking Side ID  Mounting Hole Diameter  0.113" (2.87mm)  Board Thickness  0.125" (3.18mm)  Contact Material  Brass  Contact Finish  Tin  Contact Finish Thickness  -  Insulation  Non-Insulated	Mounting Type	Through Hole
Diameter - Turret Head  O.140" (3.56mm)  Staking Side OD  O.110" (2.79mm)  Staking Side ID  - Mounting Hole Diameter  O.113" (2.87mm)  Board Thickness  O.125" (3.18mm)  Contact Material  Brass  Contact Finish  Tin  Contact Finish Thickness  - Insulation  Non-Insulated	Termination	Staking Flare
Staking Side OD  Staking Side ID  Mounting Hole Diameter  0.113" (2.87mm)  Board Thickness  0.125" (3.18mm)  Contact Material  Brass  Contact Finish  Tin  Contact Finish Thickness  -  Insulation  Non-Insulated	Flange Diameter	0.187" (4.75mm)
Staking Side ID  Mounting Hole Diameter  0.113" (2.87mm)  Board Thickness  0.125" (3.18mm)  Contact Material  Brass  Contact Finish  Tin  Contact Finish Thickness  - Insulation  Non-Insulated	Diameter - Turret Head	0.140" (3.56mm)
Mounting Hole Diameter 0.113" (2.87mm)  Board Thickness 0.125" (3.18mm)  Contact Material Brass  Contact Finish Thickness -  Insulation Non-Insulated	Staking Side OD	0.110" (2.79mm)
Board Thickness 0.125" (3.18mm)  Contact Material Brass  Contact Finish Thickness -  Insulation Non-Insulated	Staking Side ID	-
Contact Material Brass Contact Finish Tin Contact Finish Thickness - Insulation Non-Insulated	Mounting Hole Diameter	0.113" (2.87mm)
Contact Finish Contact Finish Thickness - Insulation Non-Insulated	Board Thickness	0.125" (3.18mm)
Contact Finish Thickness - Insulation Non-Insulated	Contact Material	Brass
Insulation Non-Insulated	Contact Finish	Tin
	Contact Finish Thickness	-
Report errors?	Insulation	Non-Insulated
report errors.		Report errors?

### 1519-4 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 1519-4 Payment Methods



















# 1519-4 Shipping Methods













If you have any question about 1519-4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com