

15220105601000

a Quote

15220105601000 Information

Contraction for the second for the s	Part Number	15220105601000	
	Manufacturer	HARTING	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	STRAIGHT FEMALE 9.05MM	
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact	
		us	
		Website: https://www.heisener.com	Request a
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



15220105601000 Specifications

Manufacturer Part Number15220105601000ManufacturerHARTINGCategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Serieshar-flex?Connector TypeReceptacleContact TypeReceptacleYoldBoard or CableNumber of PositionsJ0Number of Positions LoadedAllPich - Mating0.050" (1.27mm)Number of Rows2Row Spacing - MatingSolderYoldSolderFreminationSolderFastening TypeSurface MountContact Finish Thickness - MatingGoldContact Finish Thickness - MatingJackInsulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - PostSife" < - 125°CMaterial Femmability RatingLil 94 V-0		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series har-flex? Connector Type Receptacle Contact Type Receptacle Contact Type Board to Board or Cable Number of Positions 0 Number of Positions Loaded All Number of Rows 2 Row Spacing - Mating 0.050° (1.27mm) Number of Rows 2 Row Spacing - Mating 0.050° (1.27mm) Mounting Type Surface Mount Yaree Mount Solder Fremination Solder Contact Finish - Mating Gold Contact Finish Thickness - Mating Alu(0.06µm) Insulation Color Black Insulation Height 0.356° (9.05mm) Contact Length - Post - Operating Temperature -S5°C ~ 125°C	Manufacturer Part Number	15220105601000
Ackage . Series har-flex? Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.050° (1.27mm) Number of Rows 2 Row Spacing - Mating 0.050° (1.27mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 3.36° (9.05mm) Insulation Color Black Insulation Height 0.356° (9.05mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C	Manufacturer	HARTING
Package-Serieshar-flex?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions10Number of Positions LoadedAllPich - Mating0.050° (1.27mm)Number of Rows2Row Spacing - Mating0.050° (1.27mm)Mounting Type0.050° (1.27mm)Yenning TypeSolderForminationSolderFortart Finsh - MatingGoldContact Finish - MatingGoldContact Finish Thickness - MatingJackInsulation ColorJackInsulation Height0.356° (9.05mm)Contact Length - Post-Specing Type-SolderSolderSolder Solder-Solder Solder- <td< td=""><td>Category</td><td>Connectors, Interconnects</td></td<>	Category	Connectors, Interconnects
Serieshar-flex?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions10Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSolderFerminationSolderFortart Finish - MatingGoldContact Finish - MatingGoldContact Finish - Mating2.4µin (0.6µm)Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Contact Length - Post-SolerSolderContact Finish Tickness - MatingSolderContact Finish TicknessSolderContact Finish TicknessSolderContact Finish TicknessSolderContact Finish TicknessSolderContact Finish TicknessSolderC		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions10Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSolferTerminationSolderFortact Finish - MatingSolderContact Finish - MatingGoldKontact Finish - MatingGoldInsulation ColorJackInsulation Height0.356" (0.05mm)Contact Length - Post-Songer Color-Songer Color- <td< td=""><td>Package</td><td>-</td></td<>	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions10Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - Mating0.050" (0.06µm)Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Sperating Temperature-55°C ~ 125°C	Series	har-flex?
StyleBoard to Board or CableNumber of Positions10Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Connector Type	Receptacle
Number of Positions10Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - Mating2.4µin (0.06µm)Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Solder Schler Schler-Solder Schler Schler-Solder Schler Schler-Solder Schler Schler-Solder Schler Schler-Solder Schler-Schler Schler-Schler Schler-Schler Schler-Schler Schler-Schler Schler-Schler Schler-Schler Schler-Schler <td< td=""><td>Contact Type</td><td>Female Socket</td></td<>	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation ColorJ.356" (9.05mm)Contact Length - Post-Contact Length - Post-Solder- <t< td=""><td>Style</td><td>Board to Board or Cable</td></t<>	Style	Board to Board or Cable
Pitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJackInsulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-55°C ~ 125°C	Number of Positions	10
Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating2.4µin (0.06µm)Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating2.4µin (0.06µm)Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.050" (1.27mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating2.4µin (0.06µm)Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating2.4µin (0.06µm)Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.050" (1.27mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating2.4µin (0.06µm)Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating2.4µin (0.06µm)Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating2.4µin (0.06µm)Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	2.4µin (0.06µm)
Contact Length - Post-Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.356" (9.05mm)
	Contact Length - Post	-
Material Flammability Rating UII 94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	10.8mm ~ 13.8mm
Ingress Protection	-
Features	Board Guide, Pick and Place, Solder Retention
	Deport emers?

Report errors?

15220105601000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

15220105601000 Payment Methods



If you have any question about 15220105601000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com