



15220686601000 Information

Heisener.com

For Reference Only

Part Number 15220686601000

Manufacturer HARTING

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description HAR-FLEX PCR F 9.05MM 68P PL2 28

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









15220686601000 Specifications

Manufacturer Part Number 15220686601000 Manufacturer HARTING Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Scries har-flex? Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 68 Number of Positions Loaded All Pitch - Mating 0.050" (1.27mm) Number of Rows 2 Row Spacing - Mating 0.050" (1.27mm) Mounting Type Surface Mount Testening Type Surface Mount Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.356" (9.05mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C Material Flammability Rating UL94 V-0		
Category Connectors, Interconnects Package - Series har-flex? Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 68 Number of Positions Loaded All Pitch - Mating 0.050" (1.27mm) Number of Rows 2 Row Spacing - Mating 0.050" (1.27mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.356" (9.05mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C	Manufacturer Part Number	15220686601000
Package-Serieshar-flex?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions68Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Manufacturer	HARTING
Package - Series har-flex? Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 68 Number of Positions Loaded All Pitch - Mating 0.050" (1.27mm) Number of Rows 2 Row Spacing - Mating 0.050" (1.27mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.356" (9.05mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C	Category	Connectors, Interconnects
Serieshar-flex?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions68Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions68Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions68Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Series	har-flex?
Style Board to Board or Cable Number of Positions 68 Number of Positions Loaded All Pitch - Mating 0.050" (1.27mm) Number of Rows 2 Row Spacing - Mating 0.050" (1.27mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.356" (9.05mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C	Connector Type	Receptacle
Number of Positions 68 Number of Positions Loaded All Pitch - Mating 0.050" (1.27mm) Number of Rows 2 Row Spacing - Mating 0.050" (1.27mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.356" (9.05mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating 0.050" (1.27mm) Number of Rows 2 Row Spacing - Mating 0.050" (1.27mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.356" (9.05mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C	Number of Positions	68
Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.050" (1.27mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.356" (9.05mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Number of Rows	2
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.356" (9.05mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C	Row Spacing - Mating	0.050" (1.27mm)
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.356" (9.05mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C	Mounting Type	Surface Mount
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.356" (9.05mm) Contact Length - Post Operating Temperature -55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.356" (9.05mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C	Fastening Type	Push-Pull
Insulation Color Black Insulation Height 0.356" (9.05mm) Contact Length - Post Operating Temperature -55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height $0.356" (9.05mm)$ Contact Length - Post - Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	-
Contact Length - Post - Operating Temperature -55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.356" (9.05mm)
	Contact Length - Post	-
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	10.8mm ~ 13.8mm
Ingress Protection	-
Features	Board Guide, Pick and Place, Solder Retention
	Report errors?

15220686601000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

15220686601000 Payment Methods



















15220686601000 Shipping Methods













If you have any question about 15220686601000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com