

1532-3 Information

www.hest.ner.com

For Reference Only

Part Number 1532-3

Manufacturer Keystone Electronics

Category Connectors, Interconnects
Terminals - Turret Connectors

Description TERM TURRET SINGLE L=5.94MM TIN

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1532-3 Specifications

Manufacturer Part Number1532-3ManufacturerKeystone ElectronicsCategoryConnectors, InterconnectsTerminals - Turret ConnectorsPackage-Series-Terminal TypeSingle EndNumber of TurretsSingleLength - Above Board0.234" (5.94mm)Length - Below Flange0.135" (3.43mm)Length - Overall0.369" (9.37mm)Mounting TypeThrough HoleTerminationStaking FlareFlange Diameter0.187" (4.75mm)Diameter - Turret Head0.145" (3.68mm)Staking Side OD0.112" (2.84mm)Staking Side ID-Mounting Hole Diameter0.116" (2.95mm)Board Thickness0.093" (2.36mm)Contact MaterialBrassContact FinishTin	1	
Category Connectors, Interconnects Package - Series - Terminal Type Single End Number of Turrets Single Length - Above Board 0.234" (5.94mm) Length - Below Flange 0.135" (3.43mm) Length - Overall 0.369" (9.37mm) Mounting Type Through Hole Termination Staking Flare Flange Diameter 0.187" (4.75mm) Diameter - Turret Head 0.145" (3.68mm) Staking Side OD 0.112" (2.84mm) Staking Side ID - Mounting Hole Diameter 0.116" (2.95mm) Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish Tin	Manufacturer Part Number	1532-3
Package - Series - Terminal Type Single End Number of Turrets Single Length - Above Board 0.234" (5.94mm) Length - Below Flange 0.135" (3.43mm) Length - Overall 0.369" (9.37mm) Mounting Type Through Hole Termination Staking Flare Flange Diameter 0.187" (4.75mm) Diameter - Turret Head 0.145" (3.68mm) Staking Side OD 0.112" (2.84mm) Staking Side ID - Mounting Hole Diameter 0.116" (2.95mm) Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish Tin	Manufacturer	Keystone Electronics
Package - Series - Terminal Type Single End Number of Turrets Single Length - Above Board 0.234" (5.94mm) Length - Below Flange 0.135" (3.43mm) Length - Overall 0.369" (9.37mm) Mounting Type Through Hole Termination Staking Flare Flange Diameter 0.187" (4.75mm) Diameter - Turret Head 0.145" (3.68mm) Staking Side OD 0.112" (2.84mm) Staking Side ID - Mounting Hole Diameter 0.116" (2.95mm) Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish Tin	Category	Connectors, Interconnects
Series - Terminal Type Single End Number of Turrets Single Length - Above Board 0.234" (5.94mm) Length - Below Flange 0.135" (3.43mm) Length - Overall 0.369" (9.37mm) Mounting Type Through Hole Termination Staking Flare Flange Diameter 0.187" (4.75mm) Diameter - Turret Head 0.145" (3.68mm) Staking Side OD 0.112" (2.84mm) Staking Side ID - Mounting Hole Diameter 0.116" (2.95mm) Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish Tin		Terminals - Turret Connectors
Terminal Type Number of Turrets Single Length - Above Board Length - Below Flange Length - Overall Mounting Type Through Hole Termination Flange Diameter Flange Diameter - Turret Head Staking Side OD Staking Side OD Staking Side ID Mounting Hole Diameter Mounting Hole Diameter Board Thickness Contact Material Single End Single Board 0.234" (5.94mm) 0.135" (3.43mm) 1.770 (9.37mm) 1.770 (9	Package	-
Number of Turrets Length - Above Board Length - Below Flange 0.135" (3.43mm) Length - Overall 0.369" (9.37mm) Mounting Type Through Hole Termination Staking Flare Flange Diameter Flange Diameter 0.187" (4.75mm) Diameter - Turret Head 0.145" (3.68mm) Staking Side OD 0.112" (2.84mm) Staking Side ID Mounting Hole Diameter 0.116" (2.95mm) Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish	Series	-
Length - Above Board Length - Below Flange 0.135" (3.43mm) Length - Overall 0.369" (9.37mm) Mounting Type Through Hole Termination Staking Flare Flange Diameter 0.187" (4.75mm) Diameter - Turret Head 0.145" (3.68mm) Staking Side OD 0.112" (2.84mm) Staking Side ID - Mounting Hole Diameter 0.116" (2.95mm) Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish Tin	Terminal Type	Single End
Length - Below Flange0.135" (3.43mm)Length - Overall0.369" (9.37mm)Mounting TypeThrough HoleTerminationStaking FlareFlange Diameter0.187" (4.75mm)Diameter - Turret Head0.145" (3.68mm)Staking Side OD0.112" (2.84mm)Staking Side ID-Mounting Hole Diameter0.116" (2.95mm)Board Thickness0.093" (2.36mm)Contact MaterialBrassContact FinishTin	Number of Turrets	Single
Length - Overall Mounting Type Through Hole Termination Staking Flare Flange Diameter Flange Diameter - Turret Head O.187" (4.75mm) Diameter - Turret Head O.145" (3.68mm) Staking Side OD O.112" (2.84mm) Staking Side ID Mounting Hole Diameter O.116" (2.95mm) Board Thickness O.093" (2.36mm) Contact Material Brass Contact Finish Tin	Length - Above Board	0.234" (5.94mm)
Mounting Type Termination Staking Flare Flange Diameter Flange Diameter - Turret Head 0.145" (3.68mm) Staking Side OD Staking Side ID Mounting Hole Diameter 0.116" (2.95mm) Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish Tin	Length - Below Flange	0.135" (3.43mm)
Termination Staking Flare Flange Diameter 0.187" (4.75mm) Diameter - Turret Head 0.145" (3.68mm) Staking Side OD 0.112" (2.84mm) Staking Side ID - Mounting Hole Diameter 0.116" (2.95mm) Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish Tin	Length - Overall	0.369" (9.37mm)
Flange Diameter 0.187" (4.75mm) Diameter - Turret Head 0.145" (3.68mm) Staking Side OD 0.112" (2.84mm) Staking Side ID - Mounting Hole Diameter 0.116" (2.95mm) Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish Tin	Mounting Type	Through Hole
Diameter - Turret Head 0.145" (3.68mm) Staking Side OD 0.112" (2.84mm) Staking Side ID - Mounting Hole Diameter 0.116" (2.95mm) Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish Tin	Termination	Staking Flare
Staking Side OD Staking Side ID Mounting Hole Diameter 0.116" (2.95mm) Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish Tin	Flange Diameter	0.187" (4.75mm)
Staking Side ID Mounting Hole Diameter 0.116" (2.95mm) Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish Tin	Diameter - Turret Head	0.145" (3.68mm)
Mounting Hole Diameter0.116" (2.95mm)Board Thickness0.093" (2.36mm)Contact MaterialBrassContact FinishTin	Staking Side OD	0.112" (2.84mm)
Board Thickness 0.093" (2.36mm) Contact Material Brass Contact Finish Tin	Staking Side ID	-
Contact Material Brass Contact Finish Tin	Mounting Hole Diameter	0.116" (2.95mm)
Contact Finish Tin	Board Thickness	0.093" (2.36mm)
	Contact Material	Brass
Contact Finish This laws	Contact Finish	Tin
Contact Finish I nickness -	Contact Finish Thickness	-
Insulation Non-Insulated	Insulation	Non-Insulated
Report errors?		Report errors?

1532-3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1532-3 Payment Methods





















1532-3 Shipping Methods













If you have any question about 1532-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com