

## 153210-2020-ТВ

#### 153210-2020-TB Information

Heisener.com	Part Number Manufacturer Category Description Package	153210-2020-TB 3M Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets CONN SKT 2MM 10POS THRU-BRD SMD	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **153210-2020-TB Specifications**

Manufacturer Part Number153210-2020-TBManufacturer3MCategoryConnectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series1532Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.079" (2.00mm)Number of RowsSulface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Finish Thickness - Mating50µ/s (3.29mm)Contact Length - Post-Contact Length - Post-Contac		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series1532Connector TypeReceptacle, Bottom or Top EntryContact TypeBeade SocketStyleBoard to Board or CableNumber of Positions0Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - MatingSolderMounting TypeSolderFerminationSolderFastening TypeGoldContact Finish - MatingGoldContact Finish - MatingGoldStation ColorBlackInsulation ColorBlackStation Finish - Mating0.129" (3.29mm)Contact Length - Post-Station FinishSolderStation Finish - MatingSolderContact Finish - MatingSolderStation ColorBlackStation Finish - MatingSolderStation Finish - MatingSolderStati	Manufacturer Part Number	153210-2020-ТВ
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series1532Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountFeminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJojin (0.76µm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Manufacturer	3M
Package-Series1532Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypeQuis PublicContact Finish - MatingGoldContact Finish Thickness - MatingJojin (0.76µm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Category	Connectors, Interconnects
Series1532Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJupin (0.76µm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypeSurface MountContact Finish - MatingGoldContact Finish - MatingBlackInsulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation ColorJ12" (3.29mm)Contact Length - Post.	Series	1532
StyleBoard to Board or CableNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSurface MountFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Connector Type	Receptacle, Bottom or Top Entry
Number of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSurface MountFastening TypeSolderFontact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Number of Positions	10
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Pitch - Mating	0.079" (2.00mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Termination	Solder
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.129" (3.29mm)Contact Length - Post-	Contact Finish - Mating	Gold
Insulation Height0.129" (3.29mm)Contact Length - Post-	Contact Finish Thickness - Mating	30µin (0.76µm)
Contact Length - Post -	Insulation Color	Black
-	Insulation Height	0.129" (3.29mm)
C	Contact Length - Post	-
Operating Temperature -55°C ~ 105°C	Operating Temperature	-55°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin-Lead
Mated Stacking Heights	-
Ingress Protection	-
Features	Board Guide
	Dement enterna 2

Report errors?

# 153210-2020-TB Guarantees **Quality Guarantees** We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition. **Service Guarantees** SFRVIO We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers. 153210-2020-TB Payment Methods WIRE transfer 🗜 PayPal S MoneyGram Alipay VISA DISCOVER 153210-2020-TB Shipping Methods PHL\_

If you have any question about 153210-2020-TB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com