



155PSB850K2J Information



For Reference Only

Part Number 155PSB850K2J

Manufacturer Illinois Capacitor

Category Capacitors

Film Capacitors

Description CAP FILM 1.5UF 10% 850VDC RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









155PSB850K2J Specifications

Manufacturer Part Number 155PSB850K2J Manufacturer Illinois Capacitors Category Capacitors Package Radial Series PSB Capacitance 1.5µF Tolerance ±10% Voltage Rating - AC 500V Voltage Rating - DC 850V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.9 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.673" L x 1.102" W (42.50mm x 28.00mm) Height - Seated (Max) 1.457" (37.00mm) Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features - Features -	1331 5D030K23 Specifications		
Category Capacitors Package Radial Series PSB Capacitance 1.5µF Tolerance ±10% Voltage Rating - AC Voltage Rating - DC Bielectric Material ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.673" L x 1.102" W (42.50mm x 28.00mm) Height - Seated (Max) 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features - Capacitors Film Capacitors Radial Sove	Manufacturer Part Number	155PSB850K2J	
PackageRadialSeriesPSBCapacitance 1.5μ FTolerance $\pm 10\%$ Voltage Rating - AC $500V$ Voltage Rating - DC $850V$ Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance) 2.9 mOhm Operating Temperature -40° C ~ 100° CMounting TypeThrough HolePackage / CaseRadialSize / Dimension 1.673° L x 1.102° W ($42.50 \text{mm} \times 28.00 \text{mm}$)Height - Seated (Max) 1.457° (37.00mm)TerminationPC PinsLead Spacing 1.476° (37.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Manufacturer	Illinois Capacitor	
PackageRadialSeriesPSBCapacitance $1.5\mu F$ Tolerance $\pm 10\%$ Voltage Rating - AC $500V$ Voltage Rating - DC $850V$ Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance) 2.9 mOhm Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Mounting TypeThrough HolePackage / CaseRadialSize / Dimension $1.673^{\circ}\text{L} \times 1.102^{\circ}\text{W} (42.50 \text{mm} \times 28.00 \text{mm})$ Height - Seated (Max) 1.457° (37.00 mm)TerminationPC PinsLead Spacing 1.476° (37.50 mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Category	Capacitors	
SeriesPSBCapacitance $1.5 \mu F$ Tolerance $\pm 10\%$ Voltage Rating - AC $500V$ Voltage Rating - DC $850V$ Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance) 2.9 mOhm Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Mounting TypeThrough HolePackage / CaseRadialSize / Dimension $1.673^{\circ}\text{L} \times 1.102^{\circ}\text{W} (42.50 \text{mm} \times 28.00 \text{mm})$ Height - Seated (Max) 1.457° (37.00 mm)TerminationPC PinsLead Spacing 1.476° (37.50 mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-		Film Capacitors	
Capacitance 1.5µF Tolerance ±10% Voltage Rating - AC 500V Voltage Rating - DC 850V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.9 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.673" L x 1.102" W (42.50mm x 28.00mm) Height - Seated (Max) 1.457" (37.00mm) Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Package	Radial	
Tolerance ±10% Voltage Rating - AC 500V Voltage Rating - DC 850V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.9 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.673" L x 1.102" W (42.50mm x 28.00mm) Height - Seated (Max) 1.457" (37.00mm) Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Series	PSB	
Voltage Rating - AC Voltage Rating - DC 850V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.9 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.673" L x 1.102" W (42.50mm x 28.00mm) Height - Seated (Max) 1.457" (37.00mm) Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Capacitance	1.5μF	
Voltage Rating - DC Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.9 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.673" L x 1.102" W (42.50mm x 28.00mm) Height - Seated (Max) 1.457" (37.00mm) Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Tolerance	±10%	
Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.9 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.673" L x 1.102" W (42.50mm x 28.00mm) Height - Seated (Max) 1.457" (37.00mm) Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Voltage Rating - AC	500V	
ESR (Equivalent Series Resistance) 2.9 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.673" L x 1.102" W (42.50mm x 28.00mm) Height - Seated (Max) 1.457" (37.00mm) Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Voltage Rating - DC	850V	
Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.673" L x 1.102" W (42.50mm x 28.00mm) Height - Seated (Max) 1.457" (37.00mm) Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Dielectric Material	Polypropylene (PP), Metallized	
Mounting Type Package / Case Radial Size / Dimension 1.673" L x 1.102" W (42.50mm x 28.00mm) Height - Seated (Max) 1.457" (37.00mm) Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	ESR (Equivalent Series Resistance)	2.9 mOhm	
Package / Case Radial Size / Dimension 1.673" L x 1.102" W (42.50mm x 28.00mm) Height - Seated (Max) 1.457" (37.00mm) Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Operating Temperature	-40°C ~ 100°C	
Size / Dimension 1.673" L x 1.102" W (42.50mm x 28.00mm) Height - Seated (Max) 1.457" (37.00mm) Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Mounting Type	Through Hole	
Height - Seated (Max) Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Package / Case	Radial	
Termination PC Pins Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Size / Dimension	1.673" L x 1.102" W (42.50mm x 28.00mm)	
Lead Spacing 1.476" (37.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Height - Seated (Max)	1.457" (37.00mm)	
Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Termination	PC Pins	
Features -	Lead Spacing	1.476" (37.50mm)	
	Applications	High Frequency, Switching; High Pulse, DV/DT; Snubber	
Report errors?	Features	-	
			Report errors?

155PSB850K2J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

155PSB850K2J Payment Methods



















155PSB850K2J Shipping Methods













If you have any question about 155PSB850K2J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com