

156-14F2LC Information

Heisener.com

156-14F2LC Part Number

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 5A 110V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









156-14F2LC Specifications

Manufacturer Part Number 156-14F2LC Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series 156, CII Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 110VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In Report errors?		
Category Relays Power Relays, Over 2 Amps Package - Series 156, CII Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 110VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Manufacturer Part Number	156-14F2LC
Package - Series 156, CII Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 110VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series 156, CII Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 110VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
Series 156, CII Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 110VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10mACoil Voltage110VDCContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)11 VDCOperate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Package	-
Coil TypeNon LatchingCoil Current10mACoil Voltage110VDCContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)11 VDCOperate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Series	156, CII
Coil Current10mACoil Voltage110VDCContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)11 VDCOperate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage110VDCContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)11 VDCOperate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Coil Current	10mA
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time - Release Time - Wounting Type Socketable Termination Style 5A 240VAC - Max 82.5 VDC - 94.0 VDC Plug In	Coil Voltage	110VDC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) 11 VDC Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time - Retures - Mounting Type Socketable Termination Style 82.5 VDC 82.5 VDC - 82.5 VDC - 11 VDC - 50 Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time - Release Time - Features - Mounting Type Socketable Termination Style 11 VDC - Socketable Plug In	Switching Voltage	240VAC - Max
Operate Time - Release Time	Turn On Voltage (Max)	82.5 VDC
Release Time	Turn Off Voltage (Min)	11 VDC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	-
Mounting Type Socketable Termination Style Plug In	Release Time	-
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

156-14F2LC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

156-14F2LC Payment Methods





















156-14F2LC Shipping Methods













If you have any question about 156-14F2LC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com