

### 157.5701.6271 Information



For Reference Only

Part Number157.5701.6271ManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE STRIP 275A 48VDC BOLT MOUNT

Package Metal Strip

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **157.5701.6271 Specifications**

Manufacturer Part Number         157.5701.6271           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Beckrical, Specialty Fuses           Package         Metal Strip           Series         -           Fuse Type         Fuse Strip           Current Rating         275A           Voltage Rating - AC         -           Voltage Rating - DC         48V           Response Time         -           Applications         Lift Trucks           Features         Indicating           Class         -           Approvals         cURus           Operating Temperature         -40°C ~ 125°C           Breaking Capacity @ Rated Voltage         1.65kA           Mounting Type         Bolt Mount           Package / Case         Metal Strip           Size / Dimension         3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)           Report errors?		
CategoryCircuit ProtectionPackageMetal StripSeries-Fuse TypeFuse StripCurrent Rating275AVoltage Rating - AC-Voltage Rating - DC48VResponse Time-ApplicationsLift TrucksFeaturesIndicatingClass-ApprovalscURusOperating Temperature-40°C ~ 125°CBreaking Capacity @ Rated Voltage1.65kAMounting TypeBolt MountPackage / CaseMetal StripSize / Dimension3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Manufacturer Part Number	157.5701.6271
PackageMetal StripSeries-Fuse TypeFuse StripCurrent Rating275AVoltage Rating - AC-Voltage Rating - DC48VResponse Time-ApplicationsLift TrucksFeaturesIndicatingClass-ApprovalscURusOperating Temperature-40°C ~ 125°CBreaking Capacity @ Rated Voltage1.65kAMounting TypeBolt MountPackage / CaseMetal StripSize / Dimension3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Manufacturer	Littelfuse Inc.
Package         Metal Strip           Series         -           Fuse Type         Fuse Strip           Current Rating         275A           Voltage Rating - AC         -           Voltage Rating - DC         48V           Response Time         -           Applications         Lift Trucks           Features         Indicating           Class         -           Approvals         cURus           Operating Temperature         -40°C ~ 125°C           Breaking Capacity @ Rated Voltage         1.65kA           Mounting Type         Bolt Mount           Package / Case         Metal Strip           Size / Dimension         3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Category	Circuit Protection
Series         -           Fuse Type         Fuse Strip           Current Rating         275A           Voltage Rating - AC         -           Voltage Rating - DC         48V           Response Time         -           Applications         Lift Trucks           Features         Indicating           Class         -           Approvals         cURus           Operating Temperature         -40°C ~ 125°C           Breaking Capacity @ Rated Voltage         1.65kA           Mounting Type         Bolt Mount           Package / Case         Metal Strip           Size / Dimension         3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)		Electrical, Specialty Fuses
Fuse Type         Fuse Strip           Current Rating         275A           Voltage Rating - AC         -           Voltage Rating - DC         48V           Response Time         -           Applications         Lift Trucks           Features         Indicating           Class         -           Approvals         cURus           Operating Temperature         -40°C ~ 125°C           Breaking Capacity @ Rated Voltage         1.65kA           Mounting Type         Bolt Mount           Package / Case         Metal Strip           Size / Dimension         3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Package	Metal Strip
Current Rating 275A  Voltage Rating - AC -  Voltage Rating - DC 48V  Response Time -  Applications Lift Trucks  Features Indicating  Class -  Approvals CURus  Operating Temperature -40°C ~ 125°C  Breaking Capacity @ Rated Voltage 1.65kA  Mounting Type Bolt Mount  Package / Case Metal Strip  Size / Dimension 3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Series	-
Voltage Rating - AC  Voltage Rating - DC  48V  Response Time  - Applications  Lift Trucks  Features  Indicating  Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  - A8V  48V  - 48	Fuse Type	Fuse Strip
Voltage Rating - DC  Response Time - Applications Lift Trucks  Features Indicating Class - Approvals CuRus Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension  48V  48V  48V  48V  48V  48V  48V  48	Current Rating	275A
Response Time  Applications  Lift Trucks  Features  Indicating  Class  -  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Metal Strip  Size / Dimension  Lift Trucks  Lift Trucks  Lift Trucks  Lift Trucks  Indicating  CuRus  -  CURus  CURus  6  URus  6  Bolt Mount  1.65kA  Bolt Mount  8  Bolt Mount  1.65kA  Metal Strip  3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Voltage Rating - AC	-
Applications  Lift Trucks  Features  Indicating  Class  - Approvals  CURus  Operating Temperature  -40°C ~ 125°C  Breaking Capacity @ Rated Voltage  1.65kA  Mounting Type  Bolt Mount  Package / Case  Metal Strip  Size / Dimension  Lift Trucks  Lift Trucks  Indicating  -  Lift Trucks  Indicating  Bolt Mount  -  200	Voltage Rating - DC	48V
Features Indicating  Class -  Approvals cURus  Operating Temperature -40°C ~ 125°C  Breaking Capacity @ Rated Voltage 1.65kA  Mounting Type Bolt Mount  Package / Case Metal Strip  Size / Dimension 3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Response Time	-
Class  Approvals  CURus  Operating Temperature  -40°C ~ 125°C  Breaking Capacity @ Rated Voltage  1.65kA  Mounting Type  Bolt Mount  Package / Case  Metal Strip  Size / Dimension  3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Applications	Lift Trucks
Approvals  CURus  Operating Temperature  -40°C ~ 125°C  Breaking Capacity @ Rated Voltage  1.65kA  Mounting Type  Bolt Mount  Package / Case  Metal Strip  Size / Dimension  CURus  -40°C ~ 125°C  Breaking Capacity @ Rated Voltage  1.65kA  Mount  Bolt Mount  Bolt Mount  Metal Strip  3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Features	Indicating
Operating Temperature  -40°C ~ 125°C  Breaking Capacity @ Rated Voltage  1.65kA  Mounting Type  Bolt Mount  Package / Case  Metal Strip  Size / Dimension  3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Class	-
Breaking Capacity @ Rated Voltage 1.65kA  Mounting Type Bolt Mount  Package / Case Metal Strip  Size / Dimension 3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Approvals	cURus
Mounting Type Bolt Mount Package / Case Metal Strip Size / Dimension 3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Operating Temperature	-40°C ~ 125°C
Package / Case         Metal Strip           Size / Dimension         3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Breaking Capacity @ Rated Voltage	1.65kA
Size / Dimension 3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)	Mounting Type	Bolt Mount
· · · · · · · · · · · · · · · · · · ·	Package / Case	Metal Strip
Report errors?	Size / Dimension	3.228" L x 0.866" W x 0.413" H (82.00mm x 22.00mm x 10.50mm)
		Report errors?

### 157.5701.6271 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 157.5701.6271 Payment Methods



















## **157.5701.6271 Shipping Methods**













If you have any question about 157.5701.6271, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com