

1571552-3

1571552-3 Information

Heisener.com	 1571552-3 TE Connectivity AMP Connectors Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 14POS TIN - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1571552-3 Specifications

Manufacturer Part Number1571552-3ManufacturerTE Connectivity AMP ConnectorsCategoryConnectors, InterconnectsPackage-Series800TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - Mating-Contact Finish Thickness - Mating-Mounting TypeBeryllium CopperMounting TypeOpen FrameFeaturesOpen FrameContact Finish - Post1.100" (2.54mm)FeaturesOpen FrameForture Thish - PostSolderOrtucat Finish - PostSolderForture Thish - PostCopperMaterial - PostCopperHind - PostSolderFinish - PostSolderContact Finish Thickness - Post-Contact Finish Thickness-Contact Finish Thickness-<			
CategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-Series800TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - Mating-Contact Finish Thickness - Mating-Contact Finish Thickness - Mating-Mounting TypeBerylliun CopperFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - NotationSolderForther Sold0.100" (2.54mm)Forther Sold50 (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostCopperContact Finish Thickness - Post-Contact Finish Thickness - Post- <trt< td=""><td>Manufacturer Part Number</td><td>1571552-3</td><td></td></trt<>	Manufacturer Part Number	1571552-3	
NumberSockets for ICs, TransistorsPackage-Series800TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - Mating-Contact Finish - MatingBeryllium CopperContact Material - MatingBeryllium CopperMounting TypeOpen FrameFeaturesOpen FrameContact Finish - Post0.100" (2.54mm)Contact Finish - PostOilou" (2.54mm)FeaturesOpen FrameContact Material - MatingSolderForth - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostOilou" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finis	Manufacturer	TE Connectivity AMP Connectors	
Package-Series800TypeDIP,0.3" (7.62m) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mn)Contact Finish - Mating-Contact Finish - Mating-Contact Material - MatingBerylliun CopperMounting TypeDipe FrameFeaturesOpen FramePitch - Post0.100" (2.54mn)Contact Finish - Post0.100" (2.54mn)Features0.100" (2.54mn)Contact Finish - Post0.100" (2.54mn)Fortact Finish - Post0.100" (2.54mn)Contact Finish - P	Category	Connectors, Interconnects	
Series800TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingTinContact Finish Thickness - Mating-Contact Material - MatingBeryllium CopperMounting TypeOpen FrameFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish Thickness - MatingSolderPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post50derContact Finish Thickness - Post-Contact Finish Thickness - Post-Housing Material - PostCopperFourger Type Type Type-SolderSolderContact Material - Post-Contact Finish Thickness - Post-Contact Material - PostCopperFinish Thickness - Post-Contact Material - PostCopperFinish Thickness - Post-Contact Material - PostCopperFinish Thickness-Contact Material - PostCopperContact Material - PostCopperContact Finish Thickness-Contact Material - PostCo		Sockets for ICs, Transistors	
TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingTinContact Finish Thickness - Mating-Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish Thickness - Post-Contact Material - PostCopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 105°C	Package	-	
Number of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingTinContact Finish Thickness - Mating-Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostTinContact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Material - PostCopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 105°C	Series	800	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingTinContact Finish Thickness - Mating-Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - PostCopperContact Finish Thickness - Post-Contact Finish Thickness - PostCopperHousing Material - PostCopperForug TemperatureSolderschlentergenthalate (PCT), Polyester	Туре	DIP, 0.3" (7.62mm) Row Spacing	
Contact Finish - MatingTinContact Finish Thickness - Mating-Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - PostCopperHousing Material - PostCopperPoperating TemperaturePolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Number of Positions or Pins (Grid)	14 (2 x 7)	
Contact Finish Thickness - Mating-Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - PostCopperHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 105°C	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostCopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 105°C	Contact Finish - Mating	Tin	
Mounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - Post-Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 105°C	Contact Finish Thickness - Mating	-	
FeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostCopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 105°C	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostCopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 105°C	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostCopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 105°C	Features	Open Frame	
Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostCopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 105°C	Termination	Solder	
Contact Finish Thickness - Post-Contact Material - PostCopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 105°C	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostCopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 105°C	Contact Finish - Post	Tin	
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 105°C	Contact Finish Thickness - Post	-	
Operating Temperature $-55^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Material - Post	Copper	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
	Operating Temperature	-55°C ~ 105°C	
Report errors'			Report errors?

1571552-3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 1571552-3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com