



15NLE2150E Information

Manufa Categor Heisener.com

Part Number 15NLE2150E

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 150A 15.5KVAC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









15NLE2150E Specifications

Manufacturer Part Number15NLE2150EManufacturerLittelfuse Inc.CategoryCircuit ProtectionFlectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating150AVoltage Rating - AC15500V (15.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage60kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)Report errors?		
Category Circuit Protection Package Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 150A Voltage Rating - AC 15500V (15.5kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 60kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 2.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Manufacturer Part Number	15NLE2150E
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating150AVoltage Rating - AC15500V (15.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage60kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating150AVoltage Rating - AC15500V (15.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage60kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating150AVoltage Rating - AC15500V (15.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage60kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)		Electrical, Specialty Fuses
Fuse Type Cartridge Current Rating 150A Voltage Rating - AC 15500V (15.5kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 60kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Package	Cartridge, Non-Standard
Current Rating 150A Voltage Rating - AC 15500V (15.5kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 60kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Series	POWR-GARD?
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 15500V (15.5kV)	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Case - Case - Cartridge, Non-Standard Size / Dimension - Case	Current Rating	150A
Response Time	Voltage Rating - AC	15500V (15.5kV)
Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 60kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Voltage Rating - DC	-
Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 60kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Response Time	-
Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 60kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Applications	Transformer Protection
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard 23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 60kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Class	E
Breaking Capacity @ Rated Voltage 60kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Breaking Capacity @ Rated Voltage	60kA
Size / Dimension 23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)	Mounting Type	Holder
·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	23.875" L x 3.000" W x 6.380" H (606.43mm x 76.20mm x 162.05mm)
		Report errors?

15NLE2150E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

15NLE2150E Payment Methods



















15NLE2150E Shipping Methods













If you have any question about 15NLE2150E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com