

160312X Information

Heisener.com

For Reference Only

160312X

Part Number Manufacturer Switchcraft Inc.

Category

Switches

Toggle Switches

Description Package

SWITCH TOGGLE 2A 30V

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









160312X Specifications

Manufacturer Part Number 160312X Manufacturer Switchcraft Inc. Category Switches Package - Toggle Switches Series 16000 Circuit - Switch Function - Current Rating 2A (DC) Voltage Rating - AC - Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -		
Category Switches Package - Series 16000 Circuit - Switch Function - Current Rating 2A (DC) Voltage Rating - AC - Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Manufacturer Part Number	160312X
Package - Series 16000 Circuit - Switch Function - Current Rating 2A (DC) Voltage Rating - AC - Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Manufacturer	Switchcraft Inc.
Package - Series 16000 Circuit - Switch Function - Current Rating 2A (DC) Voltage Rating - AC - Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Category	Switches
Series 16000 Circuit - Switch Function - Current Rating 2A (DC) Voltage Rating - AC - Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -		Toggle Switches
Circuit - Switch Function - Current Rating 2A (DC) Voltage Rating - AC - Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Package	-
Switch Function - Current Rating 2A (DC) Voltage Rating - AC - Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length - Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Sundard Round Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features	Series	16000
Current Rating 2A (DC) Voltage Rating - AC - Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features - Features - AOC) ACDO Features - AOC) Features - AOC) Features - AOC) AOC) Features - AOC) F	Circuit	-
Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread Ingress Protection Features - Solder Lug - Features	Switch Function	-
Voltage Rating - DC Actuator Type Standard Round	Current Rating	2A (DC)
Actuator Type Standard Round - Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features	Voltage Rating - AC	-
Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features	Voltage Rating - DC	30V
Illumination Type, Color - Clumination Voltage (Nominal) - Mounting Type Panel Mount Style Solder Lug Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia 15/32-32 Ingress Protection - Features - Climate Solder Lug Solder Circular - 11.91mm Dia 15/32-32 Ingress Protection - Climate Solder Lug Solder Lug Solder Lug Solder Lug Solder Lug Solder Lug Solder So	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Actuator Length	-
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-Features-	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Bushing Thread Ingress Protection Features Circular - 11.91mm Dia 15/32-32	Mounting Type	Panel Mount
Bushing Thread 15/32-32 Ingress Protection - Features -	Termination Style	Solder Lug
Ingress Protection - Features -	Panel Cutout Dimensions	Circular - 11.91mm Dia
Features -	Bushing Thread	15/32-32
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

160312X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

160312X Payment Methods



















160312X Shipping Methods













If you have any question about 160312X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com