

160M14-660 Information



For Reference Only

Part Number 160M14-660

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 160A 660VAC/400VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









160M14-660 Specifications

Manufacturer Part Number 160M14-660 Manufacturer Eaton Category Circuit Protection Beckrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series - Fuse Type Cartridge Current Rating 160A Voltage Rating - AC 660V Voltage Rating - DC 400V Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA AC, 40kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.598" L (38.00mm x 66.00mm) Report errors?		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)Series-Fuse TypeCartridgeCurrent Rating160AVoltage Rating - AC660VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kA AC, 40kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.496" Dia x 2.598" L (38.00mm x 66.00mm)	Manufacturer Part Number	160M14-660
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series - Fuse Type Cartridge Current Rating 160A Voltage Rating - AC Voltage Rating - DC 400V Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features - Class - Cylindrical, Blade Terminal (Bolt) Size / Dimension I 496" Dia x 2.598" L (38.00mm x 66.00mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)Series-Fuse TypeCartridgeCurrent Rating160AVoltage Rating - AC660VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kA AC, 40kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.496" Dia x 2.598" L (38.00mm x 66.00mm)	Category	Circuit Protection
Series-Fuse TypeCartridgeCurrent Rating160AVoltage Rating - AC660VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kA AC, 40kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.496" Dia x 2.598" L (38.00mm x 66.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 160A Voltage Rating - AC 660V Voltage Rating - DC 400V Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge A00 Cartridge A160A A00 A00 A00 A00 A00 A00 A00 A00 A00	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 660V Voltage Rating - DC 400V Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 160A 160A 160A 160A 160A 160A 160A 160	Series	-
Voltage Rating - AC Voltage Rating - DC 400V Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 660V 660V 600V 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 400V 400V 400V 400V 400V 400V 600V	Current Rating	160A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) 1.496" Dia x 2.598" L (38.00mm x 66.00mm)	Voltage Rating - AC	660V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA AC, 40kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.598" L (38.00mm x 66.00mm)	Voltage Rating - DC	400V
Features - Class - Class - Composition - Class - Composition - Compositi	Response Time	-
Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage 80kA AC, 40kA DC Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.598" L (38.00mm x 66.00mm)	Applications	Electrical, Industrial
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA AC, 40kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.598" L (38.00mm x 66.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 80kA AC, 40kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.598" L (38.00mm x 66.00mm)	Class	-
Breaking Capacity @ Rated Voltage 80kA AC, 40kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.598" L (38.00mm x 66.00mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.598" L (38.00mm x 66.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.496" Dia x 2.598" L (38.00mm x 66.00mm)	Breaking Capacity @ Rated Voltage	80kA AC, 40kA DC
Size / Dimension 1.496" Dia x 2.598" L (38.00mm x 66.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.496" Dia x 2.598" L (38.00mm x 66.00mm)
		Report errors?

160M14-660 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

160M14-660 Payment Methods



















160M14-660 Shipping Methods













If you have any question about 160M14-660, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com