

1617038-8 Information

Heisener.com

Part Number 1617038-8

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 2A 26.5V

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1617038-8 Specifications

Manufacturer Part Number1617038-8ManufacturerTE Connectivity Aerospace, Defense and MarineCategoryRelaysPackage-SeriesHMB, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.86mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)1.5 VDCOperate Time5msRelease Time5msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook		
CategoryRelaysPackage-SeriesHMB, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.86mACoil Voltage26.5 VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28 VDC - NomTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)1.5 VDCOperate Time5msRelease Time5msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Manufacturer Part Number	1617038-8
Package-SeriesHMB, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.86mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)1.5 VDCOperate Time5msRelease Time5msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Series HMB, CII Relay Type General Purpose Coil Type Non Latching Coil Current 37.86mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Category	Relays
SeriesHMB, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.86mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)1.5 VDCOperate Time5msRelease Time5msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.86mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)1.5 VDCOperate Time5msRelease Time5msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Package	-
Coil Type Non Latching Coil Current 37.86mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Series	HMB, CII
Coil Current37.86mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)1.5 VDCOperate Time5msRelease Time5msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Relay Type	General Purpose
Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Current	37.86mA
Contact Rating (Current) Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Voltage	26.5VDC
Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Switching Voltage	28VDC - Nom
Operate Time 5ms Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Turn On Voltage (Max)	15 VDC
Release Time 5ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Turn Off Voltage (Min)	1.5 VDC
Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Operate Time	5ms
Mounting Type Chassis Mount Termination Style Solder Hook	Release Time	5ms
Termination Style Solder Hook	Features	Sealed - Hermetically
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Solder Hook
report errors.		Report errors?

1617038-8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1617038-8 Payment Methods



















1617038-8 Shipping Methods













If you have any question about 1617038-8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com