

1625947-3 Information

Heisener.com

1625947-3 Part Number

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 11M OHM 1% 10W

Package Axial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1625947-3 Specifications

Manufacturer Part Number1625947-3ManufacturerTE Connectivity Passive ProductCategoryResistorsPackageAxial, TubularSeriesHVR, CGSResistance11 MOhmsTolerance±1%Power (Watts)10WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension0.394" Dia x 2.756" L (10.00mm x 70.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-		
CategoryResistorsPackageAxial, TubularSeriesHVR, CGSResistance11 MOhmsTolerance±1%Power (Watts)10WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension0.394" Dia x 2.756" L (10.00mm x 70.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-	Manufacturer Part Number	1625947-3
Chassis Mount Resistors Package Axial, Tubular Series HVR, CGS Resistance 11 MOhms Tolerance ±1% Power (Watts) 10W Composition Thick Film Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0,394" Dia x 2.756" L (10.00mm x 70.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate	Manufacturer	TE Connectivity Passive Product
PackageAxial, TubularSeriesHVR, CGSResistance11 MOhmsTolerance±1%Power (Watts)10WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension0.394" Dia x 2.756" L (10.00mm x 70.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-	Category	Resistors
SeriesHVR, CGSResistance11 MOhmsTolerance±1%Power (Watts)10WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension0.394" Dia x 2.756" L (10.00mm x 70.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-		Chassis Mount Resistors
Resistance11 MOhmsTolerance±1%Power (Watts)10WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension0.394" Dia x 2.756" L (10.00mm x 70.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-	Package	Axial, Tubular
Tolerance ±1% Power (Watts) 10W Composition Thick Film Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.394" Dia x 2.756" L (10.00mm x 70.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Series	HVR, CGS
Power (Watts) Composition Thick Film Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.394" Dia x 2.756" L (10.00mm x 70.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Resistance	11 MOhms
Composition Thick Film Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.394" Dia x 2.756" L (10.00mm x 70.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Tolerance	±1%
Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.394" Dia x 2.756" L (10.00mm x 70.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Power (Watts)	10W
Operating Temperature Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.394" Dia x 2.756" L (10.00mm x 70.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Composition	Thick Film
Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.394" Dia x 2.756" L (10.00mm x 70.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Temperature Coefficient	±300ppm/°C
Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.394" Dia x 2.756" L (10.00mm x 70.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Operating Temperature	-
Mounting Feature Brackets (not included) Size / Dimension 0.394" Dia x 2.756" L (10.00mm x 70.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Features	High Voltage, RF, High Frequency
Size / Dimension 0.394" Dia x 2.756" L (10.00mm x 70.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Mounting Feature	Brackets (not included)
Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-	Size / Dimension	0.394" Dia x 2.756" L (10.00mm x 70.00mm)
Package / Case Axial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Ferrule Ends (Ferrule Ends, M5 Thread)
	Package / Case	Axial, Tubular
Report errors?	Failure Rate	-
		Report errors?

1625947-3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1625947-3 Payment Methods





















1625947-3 Shipping Methods













If you have any question about 1625947-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com