

1625950-6 Information

Heisener.com

1625950-6 Part Number

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 6M OHM 10% 30W

Package Axial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1625950-6 Specifications

| Manufacturer Part Number1625950-6ManufacturerTE Connectivity Passive ProductCategoryResistorsPackageAxial, TubularSeriesHVR, CGSResistance6 MOhmsTolerance±10%Power (Watts)30WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension0.846" Dia x 5.512" L (21.50mm x 140.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-Report errors? | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------|
| CategoryResistorsPackageAxial, TubularSeriesHVR, CGSResistance6 MOhmsTolerance±10%Power (Watts)30WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension0.846" Dia x 5.512" L (21.50mm x 140.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate- | Manufacturer Part Number | 1625950-6 |
| PackageAxial, TubularSeriesHVR, CGSResistance6 MOhmsTolerance±10%Power (Watts)30WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension0.846" Dia x 5.512" L (21.50mm x 140.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate- | Manufacturer | TE Connectivity Passive Product |
| PackageAxial, TubularSeriesHVR, CGSResistance6 MOhmsTolerance±10%Power (Watts)30WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension0.846" Dia x 5.512" L (21.50mm x 140.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate- | Category | Resistors |
| SeriesHVR, CGSResistance6 MOhmsTolerance±10%Power (Watts)30WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension0.846" Dia x 5.512" L (21.50mm x 140.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate- | | Chassis Mount Resistors |
| Resistance6 MOhmsTolerance±10%Power (Watts)30WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension0.846" Dia x 5.512" L (21.50mm x 140.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate- | Package | Axial, Tubular |
| Tolerance ±10% Power (Watts) 30W Composition Thick Film Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.846" Dia x 5.512" L (21.50mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate - | Series | HVR, CGS |
| Power (Watts) Composition Thick Film Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.846" Dia x 5.512" L (21.50mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate - | Resistance | 6 MOhms |
| Composition Thick Film Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.846" Dia x 5.512" L (21.50mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate - | Tolerance | ±10% |
| Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.846" Dia x 5.512" L (21.50mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate - | Power (Watts) | 30W |
| Operating Temperature Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.846" Dia x 5.512" L (21.50mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate - | Composition | Thick Film |
| Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.846" Dia x 5.512" L (21.50mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate - | Temperature Coefficient | ±300ppm/°C |
| Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 0.846" Dia x 5.512" L (21.50mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate - | Operating Temperature | - |
| Mounting Feature Brackets (not included) Size / Dimension 0.846" Dia x 5.512" L (21.50mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate - | Features | High Voltage, RF, High Frequency |
| Size / Dimension 0.846" Dia x 5.512" L (21.50mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate - | Coating, Housing Type | Aluminum |
| Height - Seated (Max) Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate - | Mounting Feature | Brackets (not included) |
| Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate- | Size / Dimension | 0.846" Dia x 5.512" L (21.50mm x 140.00mm) |
| Package / Case Axial, Tubular Failure Rate - | Height - Seated (Max) | - |
| Failure Rate - | Lead Style | Ferrule Ends (Ferrule Ends, M5 Thread) |
| | Package / Case | Axial, Tubular |
| Report errors? | Failure Rate | - |
| | | Report errors? |

1625950-6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1625950-6 Payment Methods



















1625950-6 Shipping Methods













If you have any question about 1625950-6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com