

162F10 Information

Heisener.com

For Reference Only

Part Number 162F10

Manufacturer Hammond Manufacturing

Category Transformers

Power Transformers

Description XFRMR LAMINATED 6VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









162F10 Specifications

Manufacturer Part Number 162F10 Manufacturer Hammond Manufacturing Category Transformers Package - Series 162 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)		
Category Transformers Power Transformers Package - Series 162 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Manufacturer Part Number	162F10
Package - Series 162 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Velight - Seated (Max) 33.32mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Manufacturer	Hammond Manufacturing
Package - 162 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 2500Vrms Weight	Category	Transformers
Series 162 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Package	-
Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Series	162
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 5V, Series 10V Parallel 1.2A, Series 600mA Dual Secondary Winding(s) Dual 6 VA Mounting Type Through Hole 9 C Pin Size / Dimension 41.28mm L x 33.32mm W 33.32mm Voltage - Isolation 0.44 lb (199.58g)	Type	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 1.2A, Series 600mA Dual Pull Pull Pull Power P	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) Voltage - Isolation Weight Dual No 8 VA 10 VA 11 VA 12 VA 13 VA 14 VA 15 VA 16 VA 17 VA 18 VA	Voltage - Secondary (Full Load)	Parallel 5V, Series 10V
Secondary Winding(s) Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight	Current - Output (Max)	Parallel 1.2A, Series 600mA
Center TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)33.32mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Center Tap	No
Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Power - Max	6 VA
Size / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)33.32mmVoltage - Isolation2500VrmsWeight0.44 lb (199.58g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 33.32mm 2500Vrms 0.44 lb (199.58g)	Termination Style	PC Pin
Voltage - Isolation 2500Vrms Weight 0.44 lb (199.58g)	Size / Dimension	41.28mm L x 33.32mm W
Weight 0.44 lb (199.58g)	Height - Seated (Max)	33.32mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	0.44 lb (199.58g)
		Report errors?

162F10 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

162F10 Payment Methods





















162F10 Shipping Methods













If you have any question about 162F10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com