

Heisener.com

162J10 Information

Part Number 162J10

Manufacturer Hammond Manufacturing

Category Transformers

Power Transformers

Description XFRMR LAMINATED 36VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









162J10 Specifications

Manufacturer 162J10 Manufacturer Hammond Manufacturing Category Transformers Power Transformers Package - Series 162 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 7.2A, Series 3.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.70mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)		
Category Transformers Power Transformers Package - Series 162 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 7.2A, Series 3.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.70mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Manufacturer Part Number	162J10
Package - Series 162 Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 7.2A, Series 3.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Veight Tessel 10V Power Transformers	Manufacturer	Hammond Manufacturing
Package - Series 162 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 7.2A, Series 3.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.70mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Category	Transformers
Series 162 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 7.2A, Series 3.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.70mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 7.2A, Series 3.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.70mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 7.2A, Series 3.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Voltage Secondary (Full Load) Parallel 5V, Series 10V Parallel 7.2A, Series 2.6A Primary Winding Series 2.6A Primary Wind	Series	162
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 5V, Series 10V Parallel 7.2A, Series 3.6A Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight Parallel 5V, Series 10V Parallel 5V, Series 2.6A Dual Secondary Winding(s) Dual Secondary Winding(s) 10	Туре	Laminated Core
Current - Output (Max) Parallel 7.2A, Series 3.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight 1.1 lbs (499g)	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Dual No Powal No 86 VA Through Hole PC Pin 66.68mm L x 55.55mm W 39.70mm 2500Vrms 1.1 lbs (499g)	Voltage - Secondary (Full Load)	Parallel 5V, Series 10V
Secondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.70mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Current - Output (Max)	Parallel 7.2A, Series 3.6A
Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.70mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight 36 VA PC Pin 66.68mm L x 55.55mm W 39.70mm 1.1 lbs (499g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Center Tap	No
Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.70mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Power - Max	36 VA
Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.70mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 39.70mm 2500Vrms 1.1 lbs (499g)	Termination Style	PC Pin
Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Size / Dimension	66.68mm L x 55.55mm W
Weight 1.1 lbs (499g)	Height - Seated (Max)	39.70mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	1.1 lbs (499g)
		Report errors?

162J10 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

162J10 Payment Methods





















162J10 Shipping Methods













If you have any question about 162J10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com