

### 164J28 Information

Heisener.com

Part Number 164J28

Manufacturer Hammond Manufacturing

**Category** Transformers

**Power Transformers** 

**Description** XFRMR LAMINATED 36VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 164J28 Specifications

Manufacturer Part Number       164J28         Manufacturer       Hammond Manufacturing         Category       Transformers         Package       -         Series       164         Type       Laminated Core         Voltage - Primary       115V         Voltage - Secondary (Full Load)       Parallel 14V, Series 28V         Current - Output (Max)       Parallel 2.6A, Series 1.3A         Primary Winding(s)       Single         Secondary Winding(s)       Dual         Center Tap       No         Power - Max       36 VA         Mounting Type       Through Hole         Termination Style       PC Pin         Size / Dimension       66.68mm L x 55.55mm W         Height - Seated (Max)       39.70mm         Voltage - Isolation       2500Vrms         Weight       1.1 lbs (499g)		
CategoryTransformersPackage-Series164TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 2.6A, Series 1.3APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.70mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Manufacturer Part Number	164J28
Package - Series 164 Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Power Transformers	Manufacturer	Hammond Manufacturing
Package-Series164TypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 2.6A, Series 1.3APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.70mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Category	Transformers
Series         164           Type         Laminated Core           Voltage - Primary         115 V           Voltage - Secondary (Full Load)         Parallel 14V, Series 28 V           Current - Output (Max)         Parallel 2.6A, Series 1.3A           Primary Winding(s)         Single           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         36 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         66.68mm L x 55.55mm W           Height - Seated (Max)         39.70mm           Voltage - Isolation         2500 Vrms           Weight         1.1 lbs (499g)		Power Transformers
Type Laminated Core  Voltage - Primary 115V  Voltage - Secondary (Full Load) Parallel 14V, Series 28V  Current - Output (Max) Parallel 2.6A, Series 1.3A  Primary Winding(s) Single  Secondary Winding(s) Dual  Center Tap No Power - Max 36 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 66.68mm L x 55.55mm W  Height - Seated (Max) 39.70mm  Voltage - Isolation 2500Vrms  Weight 1.1 lbs (499g)	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 14V, Series 28V  Current - Output (Max)  Parallel 2.6A, Series 1.3A  Primary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  Weight  1.1 lbs (499g)	Series	164
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 2.6A, Series 1.3A  Primary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  Weight  Parallel 14V, Series 28V  Parallel 14V, Series 1.3A  Primary Winding(s)  Dual  Center Tap  No  36 VA  Mounting Type  Through Hole  PC Pin  Size / Dimension  66.68mm L x 55.55mm W  Height - Seated (Max)  39.70mm  Voltage - Isolation  1.1 lbs (499g)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style Size / Dimension Woltage - Isolation Voltage - Isolation Weight Parallel 2.6A, Series 1.3A Primary Winding(s) Single No Poual No Poual No Poual No Poual No Poual No Sie VA Mounting Type Through Hole PC Pin Size / Dimension 66.68mm L x 55.55mm W 19.70mm 2500Vrms Voltage - Isolation 1.1 lbs (499g)	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Single No Single N	Voltage - Secondary (Full Load)	Parallel 14V, Series 28V
Secondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.70mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Current - Output (Max)	Parallel 2.6A, Series 1.3A
Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.70mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Primary Winding(s)	Single
Power - Max  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  66.68mm L x 55.55mm W  Height - Seated (Max)  Voltage - Isolation  Voltage - Isolation  Weight  36 VA  PC Pin  66.68mm L x 55.55mm W  39.70mm  1.1 lbs (499g)	Secondary Winding(s)	Dual
Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 66.68mm L x 55.55mm W  Height - Seated (Max) 39.70mm  Voltage - Isolation 2500Vrms  Weight 1.1 lbs (499g)	Center Tap	No
Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.70mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Power - Max	36 VA
Size / Dimension 66.68mm L x 55.55mm W  Height - Seated (Max) 39.70mm  Voltage - Isolation 2500Vrms  Weight 1.1 lbs (499g)	Mounting Type	Through Hole
Height - Seated (Max)  Voltage - Isolation  Veight  39.70mm  2500Vrms  1.1 lbs (499g)	Termination Style	PC Pin
Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Size / Dimension	66.68mm L x 55.55mm W
Weight 1.1 lbs (499g)	Height - Seated (Max)	39.70mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	1.1 lbs (499g)
		Report errors?

#### 164J28 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **164J28 Payment Methods**





















## 164J28 Shipping Methods













If you have any question about 164J28, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com