

### **16LCT Information**

w.heisener.com

For Reference Only

Part Number 16LCT Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 16A 240VAC/150VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **16LCT Specifications**

Manufacturer Part Number16LCTManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesLCTFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.331" Dia x 1.102" L (8.40mm x 28.00mm)Report errors?		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesLCTFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Manufacturer Part Number	16LCT
PackageElectrical, Specialty FusesSeriesLCTFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesLCTFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Category	Circuit Protection
SeriesLCTFuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.331" Dia x 1.102" L (8.40mm x 28.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating16AVoltage Rating - AC240VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 240V  Voltage Rating - DC 150V  Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  16A  A0  CHOW  CHOW	Series	LCT
Voltage Rating - AC  Voltage Rating - DC  150V  Response Time  - Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  240V  150V  150V  150V  150V  160V  16	Fuse Type	Cartridge
Voltage Rating - DC  Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  150V  150V  150V  160V	Current Rating	16A
Response Time - Applications Electrical, Industrial - Class - Class - CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - 0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Voltage Rating - AC	240V
Applications Electrical, Industrial  Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Voltage Rating - DC	150V
Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Response Time	-
Class - CE, UR  Operating Temperature - Streaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Applications	Electrical, Industrial
Approvals  CE, UR  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  O.331" Dia x 1.102" L (8.40mm x 28.00mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Approvals	CE, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.331" Dia x 1.102" L (8.40mm x 28.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.331" Dia x 1.102" L (8.40mm x 28.00mm)
		Report errors?

### **16LCT Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **16LCT Payment Methods**



















## **16LCT Shipping Methods**













If you have any question about 16LCT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com