



1706R1C5.5 Information

Manufact Category

Part Number 1706R1C5.5

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 170A 5.5KVAC NONSTD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1706R1C5.5 Specifications

Manufacturer Part Number1706R1C5.5ManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating170AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating170AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Manufacturer Part Number	1706R1C5.5
Beaking Capacity @ Rated Voltage Breaking Capacity @ Rated Voltage Breaking Capacity @ Rated Voltage Breaking Type Electrical, Specialty Fuses Cartridge, Non-Standard POWR-GARD? FOWR-GARD? Cartridge Cartridge Cartridge Cartridge Cartridge 170A 5500V (5.5kV) Voltage Rating - AC 5500V (5.5kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Apon-Standard Size / Dimension Size / Dimension Size / Dimension Cartridge, Non-Standard Size / Dimension Size / Dimension Cartridge, Non-Standard Size / Dimension Size / Dimension	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 170A Voltage Rating - AC 5500V (5.5kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating170AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating170AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC S500V (5.5kV) Voltage Rating - DC	Series	POWR-GARD?
Voltage Rating - AC Voltage Rating - DC Response Time Applications Motor Protection Features Indicating Class R Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 5500V (5.5kV)	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cartridge, Non-Standard - Cartridge, Non	Current Rating	170A
Response Time Applications Motor Protection Features Indicating Class R Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension	Voltage Rating - AC	5500V (5.5kV)
Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Voltage Rating - DC	-
Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Response Time	-
Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Applications	Motor Protection
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Class	R
Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	3.000" Dia x 15.875" L (76.20mm x 403.23mm)
		Report errors?

1706R1C5.5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1706R1C5.5 Payment Methods



















1706R1C5.5 Shipping Methods













If you have any question about 1706R1C5.5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com