

170M1315

170M1315 Information



Part Number	170M1315	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 63A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M1315 Specifications

Manufacturer Part Number170M1315ManufacturerEatonCategoryCircuit ProtectionPackageElectrical, Specialty FusesPackageRetangular, BladeSeries-Fuse TypeSquareOurrent RatingGalaVoltage Rating - ACC-Voltage Rating - DCC-Applications-Fuser Type-Carsen Type-Pactage-Pactage Type-Pactage Type-<		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSories-Fuse TypeSquareFuse TypeSquareCurrent Rating63AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialFatures-Class-ApprovalsCE CSA, UROperating Temperature000ABreaking Capacity @ Rated Polication-ApprovalsCE CSA, UROperating Temperature000AMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension1.26° L x 0.827" W x 1.575" H (54.00mm x 40.00mm)	Manufacturer Part Number	170M1315
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating63AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating TemperatureSolokABreaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating63AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Operating Temperature-Operating Temperature200KAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 40.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating63AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature900KABreaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 40.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingG3AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBoltPockage / CaseRectangulant, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 40.00mm)	Package	Rectangular, Blade
Current Rating63AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBoltMounting TypeBoltPackage / CaseRectanguland, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 40.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBoltMounting TypeBoltPackage / CaseRectangulandeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 40.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBoltMounting TypeBoltStackage / CaseRectangulandeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 40.00mm)	Current Rating	63A
Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Voltage Rating - DC	-
Features-Features-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Response Time	-
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 40.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Approvals	CE, CSA, UR
Mounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Mounting Type	Bolt
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)
		Report errors?

170M1315 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M1315, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com