

# 170M1415

#### 170M1415 Information



For Reference Only

Part Number	170M1415	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 63A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 170M1415 Specifications

Manufacturer Part Number170M1415ManufacturerEatonCategoryCircuit ProtectionPackageRectanglang BadePackageSectanglang BadeStries-Fuse TypeSquareOurrent RatingSolVoltage Rating - ACC-Voltage Rating - ACC-Stries-Applications-Applications-Carsen Same-Approvals-Ourant Same-Approvals-Carsen Same-Approvals- <tr< th=""><th></th><th></th></tr<>		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse Type63AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialApplicationsElectrical, IndustrialFaturesIndicatingOperating Temperature-ApprovalsCE, CSA, UROperating TemperatureSouldMounting TypeBoltPackage / CaseRectangular, BladeSize / DimensionStock ST, Wa L, Stor, Wa L	Manufacturer Part Number	170M1415
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating63AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurren Rating63AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature300KAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 40.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating63AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature900KABreaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 40.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingG3AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kAFeatures200kAMounting TypeBoltPackage / CaseRectanguland, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 40.00mm)	Package	Rectangular, Blade
Current RatingGAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBoltMounting TypeBoltPackage / Case2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBoltNounting TypeBoltSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 40.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageOblaMounting TypeBoltPackage / CaseRectangulandeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 40.00mm)	Current Rating	63A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Response Time	-
Class -   Approvals CE, CSA, UR   Operating Temperature -   Breaking Capacity @ Rated Voltage 200kA   Mounting Type Bolt   Package / Case Rectangular, Blade   Size / Dimension 2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Approvals	CE, CSA, UR
Mounting TypeBoltPackage / CaseRectangular, BladeSize / Dimension2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Operating Temperature	-
Package / Case   Rectangular, Blade     Size / Dimension   2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)	Mounting Type	Bolt
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.126" L x 0.827" W x 1.575" H (54.00mm x 21.00mm x 40.00mm)
		Report errors?

#### 170M1415 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

#### Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M1415, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com