

170M3019 Information



For Reference Only

Part Number 170M3019 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE SQ 400A 700VAC RECTANGULAR

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









170M3019 Specifications

Manufacturer Part Number 170M3019 Manufacturer Eaton Category Circuit Protection Package Rectangular, Blade Series - Fuse Type Square Current Rating 400A Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Manufacturer Part Number	170M3019
Package Rectangular, Blade Series - Fuse Type Square Current Rating 400A Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension Issues Square Rectangular, Blade Size / Dimension 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareCurrent Rating400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Package	Rectangular, Blade
Current Rating 400A Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Series	-
Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Indicating Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 700V 700V 700V CE, CSA, UR - CB, CSA, UR - CE, CSA, UR -	Fuse Type	Square
Voltage Rating - DC Response Time Applications Electrical, Industrial Features Indicating Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension - Breaking Capacity @ Rated Voltage Rectangular, Blade Size / Dimension - Size / Dimension	Current Rating	400A
Response Time Applications Electrical, Industrial Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension - Electrical, Industrial Electrical, Industrial Electrical, Industrial Electrical, Industrial Electrical, Industrial Approvals CE, CSA, UR CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Bolt Mount 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Voltage Rating - AC	700V
Applications Electrical, Industrial Features Indicating Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Voltage Rating - DC	-
Features Indicating Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Response Time	-
Class - CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Rectangular, Blade Size / Dimension CE, CSA, UR - Bolt Mount - Breaking Capacity @ Rated Voltage Bolt Mount Bolt Mount Rectangular, Blade 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Approvals	CE, CSA, UR
Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)
		Report errors?

170M3019 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

170M3019 Payment Methods



















170M3019 Shipping Methods













If you have any question about 170M3019, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com