


170M3110

Request a Quote

170M3110 Information



Part Number	170M3110	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 63A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M3110 Specifications

Manufacturer Part Number170M3110ManufacturerEatonCategoryCircuit ProtectionBeletrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent RatingG3AVoltage Rating + DC-Voltage Rating + DC-Specialty Fuses-Stating + DC-Voltage Rating + DC-Series-Stating + DC-Series-Stating + DC-Specialty + DC-Specialty + DC-Stating + DC-Specialty + DC- <th></th> <th></th>		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFurent Rating63AVoltage Rating - AC70VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFaturesIndicatingApprovalsCC, SA, UROperating Temperature-ApprovalsCB, SA, URNouting Type-Autoning Type-Stanger CategorySide MontFackage / CaseSide MontFackage / CaseSide MontSize / Dimension1969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm)	Manufacturer Part Number	170M3110
FieldElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating63AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature300KABreaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1,772" W x 2,283" H (50.00mm x 45.00mm x 55.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating63AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating TemperatureSolt AutomationBreaking Capacity @ Rated VoltageDokAMounting TypeBolt MountPackage / CaseRectangulageSize / Dimension1.969" Lx 1.772" W x 2.283" H (50.00mm x 45.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating63AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature90kAMounting TypeBolt MountPackage / CaseRectangulang BaleSize / Dimension1,909" L x 1.772" W x 2.283" H (50.00mm x 45.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingG3AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Apadity OperatureSolt AnnoHounting TypeBol MountPackage / CaseRectangual BalageSize / Dimension1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm)	Package	Rectangular, Blade
Current RatingGAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Beaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseIndicating RestanceSize / Dimension1,969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 55.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangular BladeSize / Dimension1.969" L x 1.77" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.77" W x 2.283" H (50.00mm x 45.00mm x 55.00mm)	Current Rating	63A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1,772" W x 2,283" H (50.00mm x 45.00mm x 58.00mm)	Voltage Rating - DC	-
FeaturesIndicatingFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Response Time	-
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 1.772" W x 2.283" H (50.00mm x 45.00mm x 58.00mm)
		Report errors?

170M3110 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M3110, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com