

170M3196

170M3196 Information



Part Number	170M3196	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 315A 1.3KVAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M3196 Specifications

Manufacturer Part Number170M3196ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC-Applications-Applications-Features-ApprovalsElectrical, IndustrialOperating Temperature-Approvals-Operating Temperature-Apontog Temperature-Autoning Type-Autoning Type-		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-ApplicationsElectrical, IndustrialFeaturesIndicatingOperating Temperature-ApprovalsCSA, UROperating Temperature100kAMounting TypeBolt MountPackage / CaseScaugal, BladeSize / DimensionSits "La T, TZ" W x 2.283" H (80.00mm x 45.00mm)	Manufacturer Part Number	170M3196
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 58.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 58.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingS15AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBiot Mounting TypePackage / CaseScat ManualSize / DimensionS10° L x 1.772° W x 2.283° H (80.00mm x 45.00mm)	Package	Rectangular, Blade
Current Rating315AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 58.00mm)	Series	-
Voltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt Mounting TypePackage / CaseRectangulandSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 58.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00m x 45.00m x 55.00m x 55.0	Current Rating	315A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 55.00mm)	Voltage Rating - AC	1300V (1.3kV)
ApplicationsElectrical, IndustrialApplicationsIndicatingFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 55.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangulang BaleSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00m x 45.00m x 55.00m x 5	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 58.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 58.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 58.00mm)	Class	-
Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 58.00mm)	Approvals	CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 58.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 58.00mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 58.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
	Size / Dimension	3.150" L x 1.772" W x 2.283" H (80.00mm x 45.00mm x 58.00mm)
Report error		Report errors?

170M3196 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M3196, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com