

170M3361

170M3361 Information



For Reference Only

Part Number	170M3361	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 80A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M3361 Specifications

ManufacturerEatonCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Series-Surerer Rating80AVoltage Rating - DC-Voltage Rating - DC-Applications-Fleatures-Approvals-Approvals-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Breaking Capacity @ Rated Voltage-Breaking Capacity @ Rated Voltage-Breaking Capacity @ Rated Voltage-Size / Dimension-Size / Dimension<		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladePackage-Series-Fuse TypeSquareCurrent Rating80AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm)	Manufacturer Part Number	170M3361
Current RatingElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating80AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating80AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating TypeSolt Mounting TypeBreaking Capacity @ Rated Voltage200kAPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating80AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingS0AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageSolt MountPackage / CaseRectangulandSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm)	Package	Rectangular, Blade
Current Rating80AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangulandSize / Dimension1,969" L x 1,772" W x 2,323" H (50.00mm x 45.00mm x 59.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case.Size / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Current Rating	80A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Approvals	CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)
		Report errors?

170M3361 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M3361, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com