

# 170M3465

#### 170M3465 Information



Part Number	170M3465	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQUARE 200A 700VAC	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

## For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 170M3465 Specifications

Manufacturer Part Number170M3465ManufacturerEatonCategoryCircuit ProtectionBelectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareOurrent RatingOuOAVoltage Rating - ACC-Voltage Rating - ACC-Specialty Fuses-Applications-Fuser Type-Carsen Type-Applications-Approvals-Approvals-Operating Type-Operating Type-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Apple Carsen Type-Apple Carsen Type-Apple Carsen Type-Apple Carsen Type-Approvals-Apple Carsen Type-Apple Carsen Type-<		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSquareCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialResponse Time-ApplorationsElectrical, IndustrialClass-ApprovalsCSA, UROperating Temperature-Aprovals200AMunting Type-Package / CaseRectangulang AlegPackage / Case-Size / DimensionSc32" k 1.772" W x 2.008" H (59.00mm x 45.00mm)	Manufacturer Part Number	170M3465
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200KAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension3.23" L x 1.772" W x 2.008" H (59.00mm x 45.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200ABreaking Capacity @ Rated Voltage200AAMounting TypeAloderPackage / CaseRectangulan, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200KABreaking Capacity @ Rated VoltageSoltalPockage / CaseRectanguland, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Package	Rectangular, Blade
Current Rating200AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSa:23" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAHouting TypeHolderPackage / CaseRectangular BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAHounting TypeHolderPackage / CaseRectangulandeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00m x 45.00m mt x 51.00m mt x 51.00	Current Rating	200A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,323" L x 1.772" W x 2.008" H (59.00m x 45.00m m)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Approvals	CSA, UR
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade   Size / Dimension 2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)
		Report errors?

#### 170M3465 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M3465, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com