

# 170M3468

#### 170M3468 Information



Part Number	170M3468	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQUARE 350A 700VAC	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

## For Reference Only

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



#### 170M3468 Specifications

<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>		
CategoryCircuit ProtectionFackageFactarquity FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialApplicationsIdicatingClass-ApprovalsCSA, UROperating Temperature-Approvals200kAMounting TypeHolderPackage / CaseScaugular, BladeSize / DimensionS.233" Lx 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Manufacturer Part Number	170M3468
FunctionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension3.33" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00man x 45.00man x 51.00man)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent RatingStoAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectanguland, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse Type350ACurrent Rating500AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBioderMounting TypeHolderPackage / CaseScazy Lx 1.772"W x 2.008"H (59.00mm x 45.00mm)	Package	Rectangular, Blade
Current Rating350AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Fuse Type	Square
Voltage Rating - DC.Response Time.ApplicationsElectrical, IndustrialFeaturesIndicatingClass.ApprovalsCSA, UROperating Temperature.Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00m x 45.00m x 51.00m x	Current Rating	350A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00m x 45.00m x 51.00m x 5	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangulang BadeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00m x 45.00m x 51.00m x 51.00	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Approvals	CSA, UR
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade   Size / Dimension 2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
	Size / Dimension	2.323" L x 1.772" W x 2.008" H (59.00mm x 45.00mm x 51.00mm)
Report err		Report errors?

#### 170M3468 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M3468, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com