

170M3612

170M3612 Information



Part Number	170M3612	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 100A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M3612 Specifications

Manufacturer Part Number170M3612ManufacturerEatonCategoryCircuit ProtectionPackageRectanglary FusesPackageRectangulary BladeStries-Fuse TypeSquareOurrent Rating00AVoltage Rating - DC-Voltage Rating - DC-ApplicationsElectrical, IndustrialApprovals-Carsent Gargenge Part-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Applications-Approvals-A		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse Type100ACurrent Rating100AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialFatures-Class-ApprovalsCE, CSA, UROperating Temperature00AABreaking Capacity @ Rated Voltage-ApprovalsCE, CSA, UROperating Temperature00AAMounting TypeBid MountPackage / CaseRectangulangeSize / Dimension1969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm)	Manufacturer Part Number	170M3612
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating100AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurren Rating100AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Operating Temperature-Operating Temperature-Breaking Capacity @ Rated Woltage-Munting TypeBit MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating100AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature200ABreaking Capacity @ Rated VoltageSolt Mounting TypePackage / CaseRectangulang BaleSize / Dimension1,609" Lx 1,772" W x 2,323" H (50,00mm x 45,00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating100AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature200ABreaking Capacity @ Rated VoltageBiol Mounting TypePackage / CaseRectangulandeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm)	Package	Rectangular, Blade
Current Rating IOOA Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Operating Temperature - Preaking Capacity @ Rated Voltage 200kA Nounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1,969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case.Size / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Woltage-Mounting TypeBolt MountFackage / CasaRectangulandeSize / Dimension1.969" L x 1.77" W x 2.323" H (50.0000 m x 45.0000 m x 55.0000 m x 55.00000 m x 55.000000 m x 55.0000000000000000000000000000000000	Current Rating	100A
Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1,772" W x 2,323" H (50.00mm x 45.00mm x 59.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Voltage Rating - DC	-
Features-Features-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Response Time	-
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)
		Report errors?

170M3612 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M3612, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com