

170M3689

170M3689 Information



For Reference Only

Part Number	170M3689	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 63A 1.3KVAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M3689 Specifications

Manufacturer Part NumberI70M3689ManufacturerEatonCategoryCircuit ProtectionBectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent RatingG3AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-FacturesIndicatingClass-ApplicationsElectrical, IndustrialPorevalsCSA, UROperating Temperature-Resulting Capacity @ Rated Voltage100kAStating TypeBolt MountPackage / CaseSon's Unit and Son's Unit and Son		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSquareCurrent Rating63AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-ApplicationsElectrical, IndustrialResponse Time-ApplicationsElectrical, IndustrialFeaturesIndicatingOperating Temperature-ApprovalsCSA, UROperating Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2,13" L x 1.772" W x 2.323" H (74.00mn x 45.00mm)	Manufacturer Part Number	170M3689
IndependencingElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating63AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating63AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-AprovalsBiot MountMounting TypeBolt MountPackage / CaseScal Sulf Sulf Sulf Sulf Sulf Sulf Sulf Sul	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating63AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100KABreaking Capacity @ Rated VoltageBolt MountiMounting TypeBolt MountPackage / CaseSc13" L x 1.772" W x 2.323" H (74.00mm x 45.00mm)		Electrical, Specialty Fuses
Fuse Type Square Fuse Type Square Fuse Type Square Current Rating G3A Voltage Rating - AC 1300V (1.3kV) Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm)	Package	Rectangular, Blade
Current RatingGAVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case.Size / Dimension2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)	Series	-
Voltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case.Size / Dimension2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 1.772" W x 2.323" H (74.00m x 45.00m x 59.00m)	Current Rating	63A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)	Voltage Rating - AC	1300V (1.3kV)
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)	Voltage Rating - DC	-
FeaturesIndicatingFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)	Features	Indicating
AOperating TemperatureBreaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)	Class	-
Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)	Approvals	CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Papert error	Size / Dimension	2.913" L x 1.772" W x 2.323" H (74.00mm x 45.00mm x 59.00mm)
Kepon enor		Report errors?

170M3689 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M3689, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com