

170M3767

170M3767 Information



For Reference Only

Part Number	170M3767	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 315A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M3767 Specifications

ManufacturerEatonCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladePackage-PackageSquarePackageSquarePackage315AVoltage Rating - DC700VVoltage Rating - DC-Package-Package-Package-Package-Package-Package-Package-Package/Case-Package/Case-Size / Dimension-Size / Dimension-Si		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Suer TypeSquareCurrent Rating315AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature00kABreaking Capacity @ Rated VoltageSolta Mounting TypeBreakage / CaseSecting Langular, BladeSize / Dimension1,969° Lx 1.772° W x 2.323° H (50.00mm x 45.00mm x 59.00mm)	Manufacturer Part Number	170M3767
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kABreaking Capacity @ Rated Voltage200kARectangular, BladeRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC700VVoltage Rating - DC-Applications-Response Time-ApplicationsElectrical, IndustrialClass-ApprovalsCSA, UROperating Temperature-Applications TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Type200kABeaking Capacity @ Rated Voltage200kAPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)		Electrical, Specialty Fuses
Fuse Type Square Current Rating 315A Voltage Rating - AC 700V Voltage Rating - DC - Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Voltage Rateg / Case Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Package	Rectangular, Blade
Current Rating315ACurrent Rating - AC700VVoltage Rating - DC-Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangular, BladePackage / Case1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Current Rating	315A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAPackage / CaseRectangular, BladePackage / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAPackage / CaseBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeBize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Approvals	CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
	Size / Dimension	1.969" L x 1.772" W x 2.323" H (50.00mm x 45.00mm x 59.00mm)
Report errors?		Report errors?

170M3767 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M3767, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com