

# 170M4113

### 170M4113 Information



Part Number	170M4113	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 450A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

#### For Reference Only

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 170M4113 Specifications

Manufacturer Part Number170M4113ManufacturerEatonCategoryCircuit ProtectionBeletrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent RatingStoJAVoltage Rating - ACC-Voltage Rating - DCC-ApplicationsElectrical, IndustrialApprovalsElectrical, IndustrialClass-ApprovalsCircos, UROperating Temperature-Applications Qualty Back Old-ApprovalsElectrical, IndustrialOperating Temperature-ApprovalsOtoXMounting TypeBolt MountPackage / CaseRectangular, BladeSiz / DimensionIndoxSiz / Dimension-MountStoRST W 2.598" H (50.00mm x 53.00mm x 66.00mm)Marce Harter Store-Siz / Dimension-Marce Harter Store-Siz / Dimension-Siz / Di		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSquareCurrent Rating450AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Stanking Capacity @ Rated Voltage200kAMounting TypeBid MountPackage / CaseRectangular, BladeSize / Dimension1,96°'' L x 2,087'' W x 2,598''' H (50.00mm, S 50.00mm)	Manufacturer Part Number	170M4113
FunctionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating450AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,598" H (50.00mm x 53.00mm x 66.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating450AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingOperating Temperature-Operating Temperature-Operating Temperature-Nounting TypeBolt MountPackage / CaseScalugar, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 55.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating450AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kAHounting TypeBolt MountPackage / CaseRectangulang BalageSize / Dimension1,69°° Lx 2,087° W x 2,598°° H (50.00mm x 55.00mm x 66.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating450AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200AFeatures200AAMounting TypeBel MountPackage / CaseRectangulandField / CaseScole MountField / CaseBiol MountField / CaseBiol MountField / CaseScole Mount <td>Package</td> <td>Rectangular, Blade</td>	Package	Rectangular, Blade
Curren Rating450AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical IndustrialFeaturesIndicatingClass-ApprovalsCE CSA, UROperating Temperature00kAFeaturesSold MountApandarg YengBid MountApandarg YengSold MountFeaturesNover MountStack Jeng CapacitySold MountFeaturesSold MountFeaturesSold MountStack Jeng CapacitySold MountFeaturesNover MountStack Jeng CapacitySold MountFeaturesSold MountFeaturesSold MountStack Jeng CapacitySold MountStack Jeng Capacity<	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kAHounting TypeBolt MountPackage / CaseRectangular BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage00KAMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 56.00mm)	Current Rating	450A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,598" H (50.00mm x 53.00mm x 66.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,598" H (50.00mm x 53.00mm x 66.00mm)	Voltage Rating - DC	-
FeaturesIndicatingFlass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Response Time	-
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,598" H (50.00mm x 53.00mm x 66.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)
		Report errors?

#### 170M4113 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4113, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com