

170M4119

170M4119 Information



Part Number	170M4119	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 900A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M4119 Specifications

Manufacturer Part Number170M4119ManufacturerEatonCategoryCircuit ProtectionBeletrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareOurrent Rating000AVoltage Rating - DC-Voltage Rating - DC-ApplicationsElectrical, IndustrialApplicationsElectrical, IndustrialClass-Approvals-Operating Temperature-Operating Temperature-Apploxals-Approvals-Outage Rating Outage-Class-Approvals-Operating Temperature-Autoning TypeBit MountMounting TypeBit MountSize / Dimension-Size / Dimension-Mounter Streem Stre		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse Type900ACurrent Rating900AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Preaking Capacity @ Rated Voltage200AMounting Type610 MountPackage / CaseRectangular, BladeSize / Dimension1.960° L x 2.087° W x 2.598° H (50.00mm x 53.00mm x 56.00mm)	Manufacturer Part Number	170M4119
FirstElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating900AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,598" H (50.00mm x 53.00mm x 66.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating900AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 55.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating900AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature900ABiending TypeBolt MountiPackage / CaseRectangulang BieleSize / Dimension1,969° L x 2,087° W x 2,598° H (50.00mm x 55.00mm x 66.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating900AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200AFeatures200AAMounting TypeBiol MountPackage / CaseRectangulandField / CaseScole MountField / CaseScole MountField / CaseBiol MountField / CaseScole Mount<	Package	Rectangular, Blade
Curren Rating900AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature00KAFeaturesSold MontaAponta TypeBit MontaApackage / CassSecang Manage Mana	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kAHounting TypeBolt MountPackage / CaseRectangular BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage00KAMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00000000000000000000000000000000000	Current Rating	900A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,598" H (50.00mm x 53.00mm x 66.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,598" H (50.00mm x 53.00mm x 66.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Response Time	-
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,598" H (50.00mm x 53.00mm x 66.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)
		Report errors?

170M4119 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4119, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com