

170M4141

170M4141 Information



Part Number	170M4141	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 315A 1.3KVAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M4141 Specifications

ManufacturerEatonCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-SeriesSquareCurrent Rating315AVoltage Rating - AC300V (1.3kV)Voltage Rating - DC-ApplicationsElectrical, IndustrialResponse Time-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseScuspaner Time, Sub MountSize / Dimension3150'' L x 2.087'' W x 2.598'' H (80.00mm x 53.00mm x 66.00mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100AABreaking Capacity @ Rated Voltage100AAMounting TypeBolt MountPackage / CaseScatsgular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Manufacturer Part Number	170M4141
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareCurrent Rating315AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Package	Rectangular, Blade
Current Rating315AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Series	-
Voltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Current Rating	315A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Voltage Rating - AC	1300V (1.3kV)
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Class	-
Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Approvals	CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)
		Report errors?

170M4141 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4141, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com