

170M4144

170M4144 Information



Part Number	170M4144	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 450A 1.3KVAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M4144 Specifications

Manufacturer Part Number170M4144ManufacturerEatonCategoryCircuit ProtectionBeletrical, Specialty FusesPackageRetangular, BladeSeriesSquareFuse TypeSquareCurrent RatingStoMVoltage Rating + AC300V (1.3KV)Voltage Rating + DC-Specialty FusesSecrical, IndustrialApplicationsSecrical, IndustrialClass-ApprovalsSAQKUOperating TemperatureSAQKUOperating TemperatureSAQKUApprovalsSAGKUMouning TypeBit MountFackage / CaseSit MountSpecialty Specialty Special		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating450AVoltage Rating - AC300V (1.3kV)Voltage Rating - DC-ApplicationsElectrical, IndustrialApplicationsSciercial, IndustrialFeaturesIdicatingApprovals-Approvals-ApprovalsCSA, URApprovals-Approvals100kAAutoming Type-Automing TypeBiol MountAutoming TypeSci Augur, BladeAutoming TypeSci Augur, BladeFice JohnensionSci Sci Sci Sci Sci Sci Sci Sci Sci Sci	Manufacturer Part Number	170M4144
First of the second s	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating450AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature00KABreaking Capacity @ Rated VoltageBit MountMounting TypeBot MountFackage / CaseRectangulageSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 55.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareFuse TypeSquareCurrent Rating450AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangulan, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuser Type450ACurrent Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBiol MountMounting TypeBol MountPackage / CaseScacugal Rated ScaleSize / Dimension3.150" L x 2.057" W x 2.598" H (80.00mm x 56.00mm)	Package	Rectangular, Blade
Current Rating450AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangulandeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Series	-
Voltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseS.150" L x 2.087" W x 2.598" H (80.00mm x 50.00mm x 60.00mm)	Current Rating	450A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Voltage Rating - AC	1300V (1.3kV)
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Class	-
Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Approvals	CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)
		Report errors?

170M4144 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4144, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com