

### 170M4159 Information



For Reference Only

Part Number 170M4159 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE SQ 250A 700VAC RECTANGULAR

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 170M4159 Specifications

Manufacturer Part Number         170M4159           Manufacturer         Eaton           Category         Circuit Protection           Package         Rectangular, Blade           Series         -           Fuse Type         Square           Current Rating         250A           Voltage Rating - AC         700V           Voltage Rating - DC         -           Response Time         -           Applications         Electrical, Industrial           Features         Indicating           Class         -           Approvals         CE, CSA, UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         200kA           Mounting Type         Bolt Mount           Package / Case         Rectangular, Blade           Size / Dimension         1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)		
Category         Circuit Protection           Electrical, Specialty Fuses           Package         Rectangular, Blade           Series         -           Fuse Type         Square           Current Rating         250A           Voltage Rating - AC         700V           Voltage Rating - DC         -           Response Time         -           Applications         Electrical, Industrial           Features         Indicating           Class         -           Approvals         CE, CSA, UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         200kA           Mounting Type         Bolt Mount           Package / Case         Rectangular, Blade           Size / Dimension         1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Manufacturer Part Number	170M4159
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Package	Rectangular, Blade
Current Rating 250A  Voltage Rating - AC 700V  Voltage Rating - DC -  Response Time  Applications Electrical, Industrial  Features Indicating  Class  Approvals CE, CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade  Size / Dimension 1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Series	-
Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Electrical, Industrial  Indicating  Class  - Approvals  CE, CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  700V  700V  700V  6.000  CE, CSA, UR  700V  1.000	Fuse Type	Square
Voltage Rating - DC  Response Time - Applications Electrical, Industrial  Features Indicating Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension  - Breaking Capacity @ Rated Voltage Rectangular, Blade Size / Dimension  - Size / Dimension	Current Rating	250A
Response Time  Applications Electrical, Industrial  Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension  - Breaking Capacity @ Rated Voltage Response Time - Bolt Mount - Breaking Capacity @ Rated Voltage Bolt Mount - Bolt Mou	Voltage Rating - AC	700V
Applications Electrical, Industrial Features Indicating Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Voltage Rating - DC	-
Features Indicating  Class - Approvals CE, CSA, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade  Size / Dimension 1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Response Time	-
Class - CE, CSA, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Applications	Electrical, Industrial
Approvals  CE, CSA, UR  Operating Temperature  - Breaking Capacity @ Rated Voltage  Bolt Mount  Package / Case  Rectangular, Blade  Size / Dimension  CE, CSA, UR  - Bolt Mount  - Breaking Capacity @ Rated Voltage  Bolt Mount  Bolt Mount  Rectangular, Blade  1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Features	Indicating
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Rectangular, Blade  Size / Dimension  1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade  Size / Dimension 1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Approvals	CE, CSA, UR
Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Operating Temperature	-
Package / Case         Rectangular, Blade           Size / Dimension         1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)
		Report errors?

#### 170M4159 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 170M4159 Payment Methods



















## 170M4159 Shipping Methods













If you have any question about 170M4159, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com