

170M4193

170M4193 Information



Part Number	170M4193	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 400A 1.3KVAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M4193 Specifications

Manufacturer Part Number170M4193ManufacturerEatonCategoryCircuit ProtectionPackageRectangulary FusesPackageRectangulary BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - DC-Voltage Rating - DC-ApplicationsElectrical, IndustrialApprovalsElectrical, IndustrialClass-ApprovalsCSA, UROperating Temperature-Apackage Acade VoltageBiot MountApprovalsSolox Acade VoltageApprovalsScangulary BladeApunting TypeBiot MountPackage / CaseScangulary BladeSize / DimensionSize / Size		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100ABreaking Capacity @ Rated Voltage100AAMounting Type61d MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Manufacturer Part Number	170M4193
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 55.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangulang BaleSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100KAFeaking Capacity @ Rated VoltageBiol MountiMounting TypeBol MountPackage / CaseScacugular, BladeSize / Dimension3.150" L x 2.057" W x 2.598" H (80.00mm x 55.00mm x 66.00mm)	Package	Rectangular, Blade
Current Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABeaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case3.150" L x 2.087" W x 2.598" H (80.00mm x 50.00mm x 66.00mm)	Series	-
Voltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Current Rating	400A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Voltage Rating - AC	1300V (1.3kV)
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Class	-
Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Approvals	CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)
		Report errors?

170M4193 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4193, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com