

# 170M4258

#### 170M4258 Information



Part Number	170M4258	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 200A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

## For Reference Only

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



#### 170M4258 Specifications

Manufacturer Part Number170M4258ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladePackage / CaseLocy The X2, Sys" H (50,00mm x 53,00mm x 66,00mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialApplicationsIdicatingClass-ApprovalsCE, CSA, UROperating Temperature00kADireaking Capacity @ Rated Voltage-Mounting TypeBid MountPackage / CaseScangular, BladeSize / Dimension1,90°° L x 2,087° W x 2,598° H (50.00mm x 53.00mm x 66.00mm)	Manufacturer Part Number	170M4258
FieldElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating200AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBiol Mounting TypePackage / CaseSci Mounting TypeSize / Dimension1.969° L x 2.087° Wards Mounting Sci Moun	Package	Rectangular, Blade
Current Rating200AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageSolt MountPackage / CaseBot MountSize / Dimension1.60° L x 2.08° T w 2.598° H (50.00mm x 50.00mm x 60.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialApplicationsIndicatingFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kAMounting TypeBolt MountPackage / CaseRectangular BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialApplicationsIndicatingFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage00kAMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension1,969° L x 2,087° W x 2,598° H (50,00m x 53,00m x 66,00m x 100m x 1	Current Rating	200A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00m x 53.00m x 56.00m x 0.00m x 0	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Response Time	-
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00m x 53.00m x 66.00m x 00m x	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Paport arro	Size / Dimension	1.969" L x 2.087" W x 2.598" H (50.00mm x 53.00mm x 66.00mm)
Kepolt end		Report errors?

#### 170M4258 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4258, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com