

170M4462

170M4462 Information



Part Number	170M4462	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQUARE 400A 700VAC	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M4462 Specifications

Manufacturer Part Number170M4462ManufacturerEatonCategoryCircuit ProtectionPackageRectanglang BalePackageSauger BaleStriesSauger BaleSuren RatingSauger BaleVoltage Rating - ACCSauger BaleVoltage Rating - ACCSauger BaleSponser TimeSauger BaleApplicationsSchall AccString Sauger BaleSauger BaleString Sauger BaleSauger BaleApplicationsSauger BaleSponser Sauger BaleSauger Bale<		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse Type400ACurrent Rating400AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialFaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200ABreaking Capacity @ Rated Voltage200AAMounting Type61derPackage / CaseRectangular, BladeSize / Dimension1.960" L x 2.087" W x 2.717" H (50.00mm x 53.00mm)	Manufacturer Part Number	170M4462
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50.00mm x 53.00mm x 69.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurren Rating400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200KAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 59.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature900KAMounting TypeBolderPackage / CaseRectangual BaldeSize / Dimension1,690° L x 2,087° W x 2,717° H (50.00mm x 59.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAFeaking Capacity @ Rated Voltage200kANounting TypeHolderPackage / CaseRectanguland, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 59.00mm)	Package	Rectangular, Blade
Current Rating400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAReaking Capacity @ Rated VoltageBolderMounting TypeHolderPackage / CaseRectangulandeSize / Dimension1,969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAHouting TypeHolderPackage / CaseRectangulandeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAHounting TypeHolderPackage / CaseRectangulandeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 50.00mm x 69.00mm)	Current Rating	400A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50.00mm x 53.00mm x 69.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50,00mm x 53,00mm x 69,00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50,00m x 53,00m x 69,00m x 69,0	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50,00mm x 53,00mm x 69,00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Approvals	CSA, UR
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)
		Report errors?

170M4462 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4462, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com