

170M4490

170M4490 Information



Part Number	170M4490	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQUARE 250A 1.3KVAC	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M4490 Specifications

Manufacturer Part Number 170M4490 Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package Rectangular, Blade Series - Fuse Type Square Current Rating 250A Voltage Rating - AC 1300V (1.3kV) Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Operating Temperature - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Rectangular, Blade		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladePackage-Series-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialRestoresIndicatingPartersIndicatingOperating Temperature-ApprovalsCSA, UROperating Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2913" L x 2087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Manufacturer Part Number	170M4490
PackageElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Preaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 55.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated Voltage100kAMounting TypeFectangaleadePackage / CaseScaugaleadeSize / Dimension2,913" L x 2,087" W x 2,717" H (74,00mm x 53,00mm x 69,00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating250AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseScangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 55.00mm x 65.00mm)	Package	Rectangular, Blade
Current Rating250AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageHolderMounting TypeHolderPackage / Case2.913" L x 2.087" W x 2.717" H (74.00mm x 59.00mm)	Series	-
Voltage Rating - AC 1300V (1.3kV) Voltage Rating - DC - Response Time - Applications Electrical, Industrial Applications Electrical, Industrial Class - Approvals CSA, UR Operating Temperature 100kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Current Rating	250A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Voltage Rating - AC	1300V (1.3kV)
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,913" L x 2,087" W x 2,717" H (74,00mm x 53,00mm x 69,00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Class	-
Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Approvals	CSA, UR
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Mounting Type	Holder
	Package / Case Rectangular, Blade	
Report erro	Size / Dimension	2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)
		Report errors?

170M4490 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4490, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com