

# 170M4513

#### 170M4513 Information



Part Number	170M4513	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQUARE 450A 700VAC	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

## For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 170M4513 Specifications

Manufacturer Part Number170M4513ManufacturerEatonCategoryCircuit ProtectionPackageRectangulary FusesPackageRectangulary BladeStries-Fuse TypeSquareOurrent RatingSoloVoltage Rating - ACC-Voltage Rating - ACC-ApplicationsElectrical, IndustrialApprovalsElectrical, IndustrialCarsent Garage Agency-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Apple Case-Apple Case-Approvals		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSquareCurrent Rating450AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialResponse Time-ApplicationsElectrical, IndustrialFaturesIndicatingOperating Temperature-ApprovalsCSA, UROperating Temperature200AMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.71" H (50.00mm x 53.00mm)	Manufacturer Part Number	170M4513
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurren Rating450AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50.00mm x 53.00mm x 69.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurren Rating450AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200KAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 59.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating450AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature900KAMounting TypeBolderPackage / CaseRectangulang BalageSize / Dimension1,609" L x 2,087" W x 2,717" H (50.00mm x 53.00mm x 69.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating450AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAFeaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangulang BaleSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 59.00mm)	Package	Rectangular, Blade
Current Rating450AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsEcertical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature00KAReaking Capacity @ Rated Voltage10dicatingMounting TypeHolderPackage / CaseRectangulandSize / Dimension1,96° Lt 2,08° Wat 2,01° H (50,00mm x 50,00mm x 50,	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangulandeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAHounting TypeHolderPackage / CaseRectangulandeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 50.00mm x	Current Rating	450A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50.00mm x 53.00mm x 69.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50,00mm x 53,00mm x 69,00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50,00mm x 53,00mm x 69,00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Approvals	CSA, UR
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)
		Report errors?

#### 170M4513 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4513, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com