

170M4659

170M4659 Information



Part Number	170M4659	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 250A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M4659 Specifications

ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kAManufacturesSolta MountiFuseking CaseRetangular, BladePackage / CaseRetangular, Blade		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialFasturesIndicatingClass-ApprovalsCSA, UROperating Temperature000ABreaking Capacity @ Rated Voltage-Aponting TypeSolta MountPackage/ CaseSolta MountPackage/ CaseSolta MountSize / DimensionSolts" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Manufacturer Part Number	170M4659
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension5.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating TypeSold Mounting TypeBreaking Capacity @ Rated VoltageSold Mounting TypeFackage / CaseScats" L x 2.087" W x 2.717" H (136.00mm x 59.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountPackage / CaseRetangular, BladeSize / Dimension5.354" L x 2.087" W x 2.717" H (136.00mm x 59.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingStoAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangulaneSize / Dimension5.354" L x 2.087" W x 2.717" H (136.00mm x 59.00mm)	Package	Rectangular, Blade
Current Rating250AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseS34" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseS.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage00kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension5.354" L x 2.087"W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Current Rating	250A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension5.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension5.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension5.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Response Time	-
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension5.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension5.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension5.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension5.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension5.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 5.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 5.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	5.354" L x 2.087" W x 2.717" H (136.00mm x 53.00mm x 69.00mm)
		Report errors?

170M4659 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4659, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com